

TOWNSHIP 25 RANGE 01 POINT IDENTIFIER # 100440

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. for Sec. 18 only

Alias	Description
Alias	Description
Alias	Description
Alias	Description

V. W. Hosford, Surveyor - May 1949/Oct. 1950 - C.S. File 40/279 and M 12-61

I set a 1" I.P. with steel cap, from which:
A Fir 30" dia., bears S.14°W., 27.5 ft. mkd. T25S R1W ¼ S18 P.S. 253 BT.
A Fir 30" dia, bears N.57°W., 53.1 ft. mkd. T25S R1W ¼ S18 P.S. 253 BT.
Section 18 being logged and no suitable trees standing within a reasonable distance, I marked BTs in sec. 13.

BLM resurvey by James E. Jelley, Cadastral Surveyor, under Group #'s 350 and 929 - Surveyed May 1978/May 1980 - (DCSO records Vol. 42 Page(s) 16334)

Point for the ¼ sec. cor. of sec. 18 only, T25S R1W, determined at midpoint latitudinally on the W. bdy. of the sec.
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:
*T 25 S
* ¼
*S 18
*R 1 W
1978
from which
A Fir 4" dia., bears N.15½°E., 27½ lks. dist. mkd. ¼ S18 BT.
A Fir 7" dia., bears S.39°E., 49½ lks. dist. mkd. ¼ S18 BT

Fd. & used on BLM resurvey by A. Bert Skeesick & Daniel E. Weller, Cadastral Surveyors under Group #1888, surveyed Sept. 1998/Sept. 1999 - (DCSO rec. Vol. 53 Page(s) 20683-4)

Fd. ok by Ron Rice, June 2009 - M159-39

Ron Rice - For: Seneca Jones Timber Co. & Roseburg Resources Co. - Aug. 2012 - C.S. File 65/75-9

Found - 3¼" BLM Brass cap dated 1978 with the following accessories:
31" D.Fir bears S.39°E., 32.7' - healed face.
26" D.Fir bears N.15½°E., 18.2' - healed face.
1½" iron rod with 2" flat top adjacent to cap