

PRIMARY CORNER DESCRIPTION Sec. Cor. for 12 & 13 only, T25-2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by John A. McQuinn, Deputy Surveyor, under Contract #466, dated April 5, 1883 (DCSO records Vol. 8 Page(s) 3479)

Set post 4½ ft. long, 4" sq., 24" in ground for cor. to secs. 7, 12, 13 and 18, marked T25S S7 on NE.; R1W S18 on SE.; R2W S13 on SW.; and S12 on NW. faces with 2 notches on N. and 4 notches on S. edges, from which
A Fir 24" dia., bears N.60°E., 14 lks. dist. mkd. T25S R1W S7 BT.
A Fir 36" dia., bears S.75°E., 37 lks. dist. mkd. T25S R1W S18 BT.
A Fir 24" dia., bears S.50°W., 22 lks. dist. mkd. T25S R2W S13 BT.
A Maple 5" dia., bears N.80°W., 34 lks. dist. mkd. T25S R2W S12 BT.

GLO survey by Hezekiah H. Johnson, Deputy Surveyor, under Contract #721, dated May 1, 1900 - (DCSO records Vol. 8 Page(s) 3493 and 3497)

(Page 3493)
Find no trace of any line or corners.
(Page 3497)
Set a basalt stone 17x10x10 ins., 12" in the ground for cor. of secs. 7, 12, 13 and 18, marked with 2 notches on N. and 4 notches on S. edges, from which
A Fir 14" dia., bears N.19°E., 18 lks. dist. mkd. T25S R1W S7 BT.
A Hemlock 4" dia., bears S.46°E., 24 lks. dist., mkd. T25S R1W S18 BT.
A Cedar 8" dia., bears S.18°W., 43 lks. dist. mkd. T25S R2W S13 BT.
A Fir 6" dia., bears N.52°W., 21 lks. dist. mkd. T25S R2W S12 BT.

V. W. Hosford, Surveyor - May 1949/Oct. 1950 - C.S. File 40/279 and M 12-61

I set a 1" I.P. with steel cap, from which
A Fir 22" dia., bears S.51½°W., 25.5 ft. mkd. T25S R2W S13 P.S. 253 BT.
A Cedar 30" dia., bears N.73°W., 35.0 ft. mkd. T25S R2W S12 P.S. 253 BT.

Fd. OK Sept. 2, 1976 by DCSO, LE Monrean - C.S. File 59/24-18

(Cont. Next Page)

TOWNSHIP 25 RANGE 01 POINT IDENTIFIER # 100447

PRIMARY CORNER DESCRIPTION Sec. Cor. for 12 & 13 only, T25-2

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BLM resurvey by James E. Jelley, Cadastral Surveyor, under Group #'s 350 and 929 - Surveyed May 1978/May 1980 - (DCSO records Vol. 42 Page(s) 16334-35)

(81.27 chs.)

Intersect a point established by Hosford in 1950, monumented with an iron pipe 1½" dia., firmly set, projecting 10" above ground, with a steel plate, 2" sq., welded on top, mkd.

S 12 |
S 13 |
1950

from which the remains of bearing trees mkd. by Hosford:

A Fir snag 26" dia., bears S.52°W., 39 lks. dist., with fragmentary scribe marks visible on open blaze.

A sawed Cedar stump 36" dia., bears N.73°W., 55½ lks. dist. with scribe marks T25S R2W S12 PS 253 BT visible on open blaze.

(81.38 chs.) (N.0°12'W.)

Point for the cor. of secs. 12 & 13 only, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post 28" long, 2½" dia., 24" in the ground, with brass cap mkd.

T 25 S | T 25 S
S 12 | S 18
S 13 | R 1 W
R 2 W |
1978

from which

A boulder, in place, 5 x 4 x 3 ft. above ground, bears S.50½°W., 23 lks. dist. mkd. X BO on top.

No suitable trees available within limits.

Fd. & used on BLM resurvey by A. Bert Skeesick & Daniel E. Weller, Cadastral Surveyors under Group #1888, surveyed Sept. 1998/Sept. 1999 - (DCSO rec. Vol. 53 Page(s) 20684-5)