

PRIMARY CORNER DESCRIPTION C C for Secs. 6 & 7, (West)

Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Hezekiah H. Johnson, Deputy Surveyor, under Contract #721, dated May 1, 1900 - (DCSO records Vol. 9 Page(s) 3568-69)

-----  
 Intersect the W. bdy. of Tp. (T25S R1W), 7.10 chs. S. of the ¼ sec. cor. on the E. bdy. of sec. 1, T25S R2W, and at point of intersection, I Set a Chinquapin post 3 ft. long, 3" sq., 24" in the ground for closing cor. of secs. 6 & 7, mkd. CC T25S R1W on E.; S6 on N.; and S7 on S. faces, with 1 groove on N. and 5 grooves on S. faces, from which  
     A Chinquapin 5" dia., bears N.45°E., 10 lks. dist. mkd. T25S R1W S6 BT.  
     A Dogwood 4" dia., bears S.13°E., 14 lks. dist. mkd. T25S R1W S7 BT.

V. W. Hosford, Surveyor - May 1949/Oct. 1950 - C.S. File 40/279 and M 12-61

-----  
 I set a 1½" I.P. with steel cap from which  
     A Fir 16" dia., bears N.65°E., 19.7 ft. mkd. T25S R1W S6 C C P.S. 253 BT.  
     A Fir 12" dia., bears S.29°E., 13.3 ft. mkd. T25S R1W S7 C C P.S. 253 BT.

Fd. OK, DCSO, V. Tracy - May 1967 C.S. File 52/30-83

BLM resurvey by James E. Jelley, Cadastral Surveyor, under Group #1061 - Surveyed April/June 1981 - (DCSO records Vol. 45 Page(s) 17357-58)

-----  
 The closing cor., reestablished at proportionate dist. and recorded by Hosford in 1950, and accepted as the best available evidence of the position of the original corner, monumented with an iron pipe, 1½" dia., firmly set, projecting 4" above ground, from which bearing trees mkd. by Hosford:

    A Fir 22" dia., bears N.64½°E., 29 lks. dist. with healed blaze.  
     A Fir 15" dia., bears S.27½°E., 21 lks. dist. with healed blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

T 25 S	T 25 S	
R 2 W	S 6	CC
S 1	S 7	
	R 1 W	

(Cont. Next Page)

1981

TOWNSHIP 25 RANGE 01 POINT IDENTIFIER # 100600

PRIMARY CORNER DESCRIPTION C C for Secs. 6 & 7, (West)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Deposit the iron pipe alongside the iron post.

From this point, the  $\frac{1}{4}$  sec. cor. of sec. 1 only, T25S R2W bears N.0°11'W., 7.21 chs. dist.