

TOWNSHIP 25 RANGE 01 POINT IDENTIFIER # 100607

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 1 only, T25-2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM resurvey by James E. Jelley, Cadastral Surveyor, under Group #1061 - Surveyed April/June 1981 - (DCSO records Vol. 45 Page(s) 17351-52)

The ¼ sec. cor., monumented with an iron post, 2½" dia., firmly set, projecting 10" above ground with brass cap as mkd. in 1951, from which bearing trees mkd. by White and Tallett:

- A Hemlock 19" dia., bears S.29°W., 64½ lks. dist. with healed blaze. (Rec. S.28°W., 66 lks.)
- A Hemlock 28" dia., bears N.12 ¾°W., 49 lks. dist. with healed blaze.

From this point, a monument established by Hosford, in 1950, bears S.25½°E., 0.02 chs. dist. monumented with an iron pipe 1" dia., firmly set, projecting 10" above ground, from which bearing trees mkd. by Hosford:

- A Hemlock 23" dia., bears S.84°W., 21½ lks. dist. with healed blaze.
- A Hemlock 27" dia., bears N.28½°W., 55 lks. dist. with healed blaze.

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff Lorsung- 4/23/2022 (Filed 8/1120/2022) - C.S. File 67/52-45

Found - 1951 2½" GLO brass cap on 1" I.D. iron pipe proj. 6" White's BTs -
Burnt-dead 25" Hemlock S.29°W., 44.1 ft. (rec. 42.6 ft) healed blaze.

Hosford BTs -
Burnt dead 34" Hemlock S.73°W., 14.5 ft. to GLO monument (S.84°W., 14.2 ft to Hosford monument)
Hosford monument bears S.25½°E., 2.4 ft.

New - Burnt-dead 2"x30" Cedar snag N.70°W., 26.0 ft. not blazed or scribed. 3" PK right side center.
5/8"x30" iron rod with yellow plastic cap mkd: DOUG CO SURVEYOR, N.6°W., 34.0 ft. proj. 8"

Note - Monument on moderate East slope 35 ft. east of road.
Area burnt 9/2020
Compass decl. 14½°E.

Lat: 43°25'26.62"N Long: 122°52'26.76" W