

TOWNSHIP 25 RANGE 01 POINT IDENTIFIER # 100700

PRIMARY CORNER DESCRIPTION CC for Sec. 6, T25-1; & Sec. 1, T25-2

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Hezekiah H. Johnson, Deputy Surveyor, under Contract #721, dated May 1, 1900 - (DCSO records Vol. 8 Page(s) 3499)

-----  
At the point of intersection (14.05 chs. East of the SW. cor. to Tp. 24 S R 1 W), I set a basalt stone 16x9x8 ins., 11" in the ground for closing cor. of Tps. 25 S Rs 1 and 2 W., marked CC on S. face, with 6 notches on E. and W. faces, from which

- A Chinquapin 6" dia., bears S.45°E., 44 lks. dist. mkd. CC T25S R1W S6 BT.
- A Dogwood 5" dia., bears S.18°W., 39 lks. dist. mkd. CC T25S R2W S1 BT.

V.W. Hosford - April 1949/Oct. 1950 - C.S. File 40/279 and M 12-61

-----  
Set a 2" I.P. with steel cap for the closing corner from which

- A Fir 22" dia., bears S.30°E., 20.2 ft. mkd. T25S R1W S6 CC PS 253 BT.
- A Fir 24" dia., bears S.35°W., 8.7 ft. mkd. T25S R2W S1 CC PS 253 BT.

BLM resurvey by Levi E. Tallett and C. Albert White, Cadastral Surveyors, under Group #294, Surveyed May 1951/Aug. 1963 - (DCSO records Vol. 32 Page(s) 13340-41)

-----  
Porportionate point for the closing cor. of Tps. 25 S., Rs. 1 and 2 W.

Set an iron post 36" long, 3" dia., 28" in the ground with brass cap mkd. T 24 S R 1 W

S 31  
-----  
S 1 | S 6  
R 2 W | R 1 W  
T 25 S  
CC  
1951

from which

- A Fir 30" dia., bears S.41¼°E., 42 lks. dist. mkd. T25S R1W S6 CC BT.
- A Fir 26" dia., bears S.74°45'W., 19 lks. dist. mkd. T25S R2W S1 CC BT.

(The SW. cor. of T24S R1W bears S.89°51'W., 13.97 chs. dist.)

(Cont. Next Page)

TOWNSHIP 25 RANGE 01 POINT IDENTIFIER # 100700

PRIMARY CORNER DESCRIPTION CC for Sec. 6, T25-1; Sec. 1, T25-2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew  
May 5, 1967 - C.S. File 52/30-82

-----  
Found - 1951 Cadastral brass cap, properly mkd. and BTs down  
and out of place.

I.P. and steel cap bears N.21°W., 2.8 ft. The BTs  
for Hosford's corner are also dead.

New BTs- 8" Cedar S.64°W., 114.6 ft. mkd. T25S R2W S1 CC CS  
BT.

34" D.Fir S.79½°E., 41.6 ft. mkd. T25S R1W S6 CC CS  
BT.

Cadastral corner lies on East slope on cutting line, course  
E-W with timber to North.

BLM resurvey by James E. Jelley, Cadastral Surveyor, under  
Group #1061, surveyed April/June 1981 - (DCSO records Vol. 45  
Page(s) 17353-54)

-----  
The closing cor., monumented with an iron post 3" dia.,  
firmly set, projecting 2" above ground with brass cap mkd. in  
1951, from which the remains of bearing trees mkd. by White  
and Tallett:

A root hole bears S.41¼°E., 42 lks. dist. with a down  
sawed Fir stump alongside 28" dia., with scribe marks  
T25S R1W S6 BT visible on open blaze.

A root hole bears S.74 3/4°W., 19 lks. dist., with a down  
sawed Fir stump alongside, 26" dia., with fragmentary  
scribe marks visible on open blaze.

and bearing trees mkd. by Tracy in 1967:

A Fir 34" dia., bears S.73°E., 64 lks. dist., with  
fragmentary scribe marks visible on open blaze.

A Cedar 13" dia., bears S.70°W., 173 lks. dist., with  
fragmentary scribe marks visible on partially healed  
blaze.

and new bearing trees:

A Hemlock 13" dia., bears S.64½°E., 35 lks. dist. mkd.  
T25S R1W S6 CC BT.

A Hemlock 12" dia., bears S.28°W., 64 lks. dist. mkd. T25S  
R2W S1 CC BT.

From this point, a monument established by Hosford in 1950,  
bears N.16°37'W., 0.045 chs. dist., monumented with an iron  
pipe, 1" dia., with a steel cap mkd. T25S R1 R2W S1 S6 CC,  
from which the remains of BTs mkd. by Hosford

A root hole bears S.30°E., 31 lks. dist., with a down  
sawed Fir stump alongside 24" dia., with fragmentary  
scribe marks visible on open blaze.

(Cont. Next Page)

TOWNSHIP 25 RANGE 01 POINT IDENTIFIER # 100700

PRIMARY CORNER DESCRIPTION CC for Sec. 6, T25-1; Sec. 1, T25-2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A root hole bears S.35°W., 13 lks. dist. with a down Fir alongside 27" dia., no marks visible.

Douglas Co. Surveyor's Office - Crew: Stephen J. Flause and Jeff Lorsung - 11/18/2025 - C.S. File 67/61-40

-----  
Found - 3½" BLM brass cap on iron pipe set flush.  
28" x 20 ft. burnt D. Fir snag S.79½°E. 41.6 ft. burned out face but legible scribes on partly healed single blaze.  
20" x 4 ft. very burnt sawn fir stump S.41¼°E. 27.7 ft (Rec 42 lks)  
20" x 6 ft. very burnt sawn fir stump S.74¾°W. 12.5 ft. (Rec 19 lks)  
28" burned, dead, hemlock S.64½°E. 23.1 ft. (Rec 35 lks) fully healed single blaze.  
30" burned, dead, hemlock S.82°W. 42.2 ft. (Rec S.28°W. 64 lks) Fd tag reads S.82°W. Fully healed single blaze.  
Root hole S.30°E. 20.5 ft. (Rec 31 lks)  
Iron pipe with steel cap N.21°W. 2.8 ft. (BLM N.16°37'W. 0.045 lks)  
New - Sawn, singed 18" x 2 ft. fir stump S.4°W. 22.1 ft. 3½ in. Mag nail top center.  
Notes - Area badly burnt 9/2020  
Trimble GEO XT position  
43°26'15.293 N. 122°52'27.114" W.