

TOWNSHIP 25 RANGE 01 POINT IDENTIFIER # 114400

PRIMARY CORNER DESCRIPTION C 80 1/16 S18

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>BLM resurvey by A. Bert Skeesick &amp; Daniel E. Weller, Cadastral Surveyors under Group #1888, surveyed Sept. 1998/Sept. 1999 - (DCS0 rec. Vol. 53 Page(s) 20704)</p> <p>-----</p> <p>Point for the NW 1/16 sec. cor. of sec. 18, at its calculated position. Set a stainless steel post, 28" long, 2½" dia., 24" in the ground, in a collar of stone, 2 ft. dia., with brass cap mkd. T 25 S R 1 W NW 1/16 S 18 1999</p> <p>from which A fir, 8" dia., bears S.71¼°W., 15 lks mkd. NW 1/16 S18 BT A fir, 16" dia., bears N.26½°W., 11 lks mkd NW 1/16 S18 BT Deposit a magnet in a white plastic case at the base of the stainless steel post.</p>
<p>Ron Rice - For: Seneca Jones Timber Co and roseburg Resources Co. - 6/2009 - M159-39</p> <p>-----</p> <p>Found - ¾" BLM brass cap dated 1999 with the following accessories: 19" D.Fir bears N.26½°W., 7.3' - healed face 9" D.Fir bears S.71¼°W., 9.9' - healed face</p>
<p>Douglas Co. Surveyors Office - Crew: Stephen Flauser &amp; Jeff Lorsung- 5/298/2024 - C.S. File 67/58-4</p> <p>-----</p> <p>Found - ¾" 1999 BLM brass cap proj. 1" (properly mkd) Burned, dead 24" D.Fir N.26½°W., 7.5 ft. (rec. 7.3 ft.) healed face, add ¾" mag nail right side center. Burned, dead 9" D.Fir S.71¼°W., 9.9 ft. healed face, add ¾" mag nail right side center. Metal post 1.0' South.</p> <p>Note - Mon. on moderate west slope approx 125 ft. SE of grave road. Area burnt 9/2020</p> <p>Oregon Coordinate Reference System Cottage Grove - Canyonville Zone N 208546.071 E 291023.140</p>
<p>1</p>