

TOWNSHIP 25 RANGE 01 POINT IDENTIFIER # 120460

PRIMARY CORNER DESCRIPTION NW 1/16 Sec 18

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM resurvey by A. Bert Skeesick & Daniel E. Weller, Cadastral Surveyors under Group #1888, surveyed Sept. 1998/Sept. 1999 - (DCS0 rec. Vol. 53 Page(s) 20706)  
-----  
Point for the NW 1/16 sec. cor. of sec. 18, at its calculated position.  
Set a stainless steel post, 28" long, 2½" dia., 24" in the ground, in a collar of stone, 2' dia., with brass cap mkd.  
T 25 S R 1 W  
NW 1/16  
S 18  
1999  
from which  
A fir, 8" dia., bears S.71¼°W., 15 lks mkd NW 1/16 S18 BT  
A fir, 16" dia., bears N.26½°W., 11 lks mkd NW 1/16 S18 BT  
Deposit a magnet in a white plastic case at the base of the stainless steel post.

Ron Rice - For: Seneca Jones Timber Co and roseburg Resources Co. - 6/2009 - M159-39  
-----  
Found - ¾" BLM brass cap dated 1999 with the following accessories:  
19" D.Fir bears N.26½°W., 7.3' - healed face  
9" D.Fir bears S.71¼°W., 9.9' - healed face.

Douglas Co. Surveyors Office - Crew: Stephen Flauser & Jeff Lorsung- 5/28/2024 - C.S. File 67/58-4  
-----  
Found - ¾" BLM brass cap, 1999 proj. 1"  
Burned dead 24" D.Fir N.26½°W., 7.5 ft. (rec. 7.3 ft) healed face, add ¾" mag nail right side center.  
Burned dead 9" D.Fir S.71¼°W., 9.9 ft. healed face, add ¾" mag nail right side center.  
Metal post 1.0' south.  
Note - Mon. on moderate West slope approx 125 ft. SE of gravel road.  
Area burnt 9/2020  
Compass decl. 14½°E.  
Oregon Coordinate Reference System  
Cottage Grove - Canyonville Zone  
N 208546.071 E 291023.140