

TOWNSHIP 25 RANGE 01 POINT IDENTIFIER # 140100

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 31 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Hezekiah H. Johnson, Deputy Surveyor, under Contract #721, dated May 1, 1900 - (DCSO records Vol. 8 Page(s) 3505)

-----  
The point for ¼ sec. cor. falls on a basalt stone in place, 12x12x5 ft. above ground at the exact cor. point I cut on cross (+) for ¼ sec.cor., and marked on ¼ on N. side of cross, from which

- A Fir 22" dia., bears S.32°W., 18 lks. dist. mkd. ¼ S6 BT.
- A Fir 4" dia., bears N.20°W., 17 lks. dist. mkd. ¼ S31 BT.

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #797, dated April 19, 1910 - (DCSO records Vol. 9 Page(s) 3576-77) and (Duplicate Pg. 4082)

-----  
The ¼ sec. cor. on rock 12x12x5 ft., marked and witnessed as described by the surveyor general. I re-establish this cor. in its original position as the ¼ sec. cor. on S. bdy. sec. 31, T25S R1W only, as follows:

Rock, above descried, from which

- A Fir 10" dia., bears N.31½°E., 66 lks. dist. mkd. ¼ S31 BT.

A Fir 4" dia., bears N.20°W., 17 lks. mkd. ¼ S31 BT. I obliterate marks on former bearing tree referring to sec. 6.

Fd. ok by V. R. Tracy, 10/1966 C.S. File 52/30