

TOWNSHIP 25 RANGE 01 POINT IDENTIFIER # 140240

PRIMARY CORNER DESCRIPTION Center 1/4 Cor Sec 30

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

Larry J. Friar - For: Umpqua National Forest - April 1979 - M 70-70

Set - 2½" x 30" Gal. I. Pipe with 3" dia. brass cap stamped:
T25S R1W C¼ + S30 PLS 961 1979
From which:
A 8" Fir bears N.40¾°E., 13.3 ft. scribed C¼ S30 BT.
A 8" Fir bears S.0¾°E., 12.3 ft. scribed C¼ S30 BT.

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff Lorsung- 6/13/2024 - C.S. File 67/58-10

Found - 3" brass cap (properly mkd) on 2½" O.D. iron pipe up 6" in large rough stone mound.
Burned broken rotted 6"x5½ ft. fir stub N.40¾°E., 13.3 ft. blazes burned away.
Burned broken rotted 5"x3½ ft. stub S.0¾°E., 12.3 ft. all scribes visible on fire opened double blaze.
Both BTs have ¾" brass washer nailed in lower blaze stamped LS 961.
Steel fence post North 4.0 ft. with two USFS survey marker signs.
New - 30" I.R. proj 5" S.40°E., 5.5'
30" I.R. proj 5" N.80°E., 5.8'
Note - Mon near top of steep westerly slope approx 50 ft west & 20 ft lower than crest of small NNE ridge.
Mon is 175± ft north fro sharp curve in gravel rd.
Area burnt 9/2020
Compass decl. 14¾°E.
Oregon Coordinate Reference System
Cottage Grove - Canyonville Zone
N 196292.283 E 292626.435