

TOWNSHIP 25 RANGE 01 POINT IDENTIFIER # 140300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 19 & 30

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by Hezekiah H. Johnson, under Contract #721, dated May 1, 1900 (DCSO records Vol. 9 Page(s) 3558)

Set a basalt stone, 17x8x8", 11" in the ground for ¼ sec. cor. mkd. ¼ on N face, from which

A fir, 6" dia., bears N.18°W., 44 lks., mkd: ¼ S19 BT.

A fir, 5" dia., bears S.32°W., 12 lks., mkd: ¼ S30 BT.

BLM Dependent resurvey by James E. Jelley, Cadastral Surveyor under Group #350 & 929 surveyed May 1978/May 1980 - (DCSO records Vol. 42 Page(s) 16351)

Point for the ¼ sec. cor. of secs. 19 & 20, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28 long, 2½" dia., 24" in the ground with brass cap marked:

T25S R1W
¼ S 19
 S 30
1978

from which

A hemlock, 9" dia., bears N.54¾°E., 25½ lks. mkd: ¼ S19 BT

A fir, 9" dia., bears S.64°W., 54 lks., mkd: ¼ S30 BT.