TOWNSHIP 25 RANGE 01 POINT IDENTIFIER # 140340

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 19

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BLM Dependent resurvey by James E. Jelley, Cadastral Surveyor under Group #350 & 929 surveyed May 1978/May 1980 - (DCSO records Vol. 42 Page(s) 16360)

Point for the center ¼ sec. cor. of sec. 19 at intersection with the E & W center line.
Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap marked: T25S R1W
C¼ S 19
1978
from which
A fir, 7" dia., bears S.75½°E., 53½ lks., mkd: C¼ S19 BT.
A fir, 6" dia., bears S.83°W., 53½ lks., mkd: C¼ S19 BT.

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff Lorsung- 2/1/2022 (Filed 4/13/2022) - C.S. File 67/52-14

Found - 3¼" brass cap on 2½" iron pipe projecting 8" (properly mkd)
20" Burnt Fir bears S.83°W., 35.0 to 3½ PK nail RT side center (rec 53½ lks 35.2 ft)
Old root hole S.75½°E., 35.2 ft (Rec 53½ lks)
New - 17"x2½' sawn & burnt Cedar stump S.38°E., 20.4 ft. 3½" PK nail top center.
9" Hemlock S.27°W., 19.0 ft. Location tag only.
Note - Area burnt 9/2020
Compass decl. 14½°E.
See sketch in file
Lat: 43°23'08.35" N Long: 122°50'59.09" W