

TOWNSHIP 25 RANGE 01 POINT IDENTIFIER # 140640

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 6

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BLM Dependent resurvey by James E. Jelley, Cadastral Surveyor under Group #1061 surveyed April/June 1981 - (DCSO records Vol. 45 Page(s) 17360-1)

Point for the center ¼ sec. cor. of sec. 6, at intersection with the E & W center line.

Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap marked:
T25S R1W
C ¼ S 6
1981

from which

A fir, 7" dia., bears N.66½°E., 27½ lks., mkd: C¼ S6 BT.

A fir, 9" dia., bears N.37½°W., 23 lks., mkd: C¼ S6 BT.

FD. BC & 1 BT by D. Edwards, 8/2008 - M156-53 - Set 6' steel post 2' east.

Fd. BC as per M156-53 by D.Edwards, 10/2014 - C.S. 65/84-12

Gerald Nygren - For: Barnes & Associates - 12/2018 - M175-10

Found - 1981 BLM Brass cap per rec.
7" Fir, now blow down root hole bears N.66°30'E., 18.2'

9" fir, now 15" bears N.37°30'W. 15.2' healed blaze.
Fd. 5' metal post, South, 0.20'

Set - 5' galv. Metal post, East, 5.0'