

TOWNSHIP 25 RANGE 01 POINT IDENTIFIER # 160460

PRIMARY CORNER DESCRIPTION NE 1/6 Sec 18

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BLM resurvey by A. Bert Skeesick & Daniel E. Weller,
Cadastral Surveyors under Group #1888, surveyed Sept.
1998/Sept. 1999 - (DCS0 rec. Vol. 53 Page(s) 20705)

Point for the NE 1/16 sec. cor. of sec. 18, at its calculated
position.

Set a stainless steel post, 28" long, 2½" dia., 24" in the
ground, in a collar of stone, 2' dia., with brass cap mkd.

T 25 S R 1 W

NE 1/16

S 18

1999

from which

A fir, 8" dia., bears S.77½°E., 81 lks. mkd NE 1/16 S18 BT

A fir, 6" dia., bears N.30¾°W., 39 lks. mkd NE 1/16 S18 BT

Deposit a magnet in a white plastic case at the base of the
stainless steel post.

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff
Lorsung- 5/29/2024 - C.S. File 67/58-6

Found - 3¼" BLM brass cap proj 5" (properly mkd)
Burnt-sawn 14"x1 ft D.Fir stump S.77½°E., 54.3 ft.
(rec. 81 lks 54.4 ft) evidence of face inside,
add 3½" mag nail top center.

Burnt-broken 10"x4 ft. D.Fir snag down and uprooted
root hole good for B & D. N.30¾°W., 25.7 ft
evidence fo healed blaze.

Steel fence post 1.3 ft. South.

New - Burned-dead 21" D.Fir N.43°E., 42.2 ft., 3½" mag
nail right side center.

Note - Area burnt 9/2020
Compass decl. 14½°E.

Oregon Coordinate Reference System
Cottage Grove - Canyonville Zone
N 208528.031 E 293609.487