

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 31 & 32

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO Survey by Hezekiah H. Johnson, under Contract #721, dated May 1, 1900 (DCSO records Vol. 9 Page(s) 3552-3)

Set a basalt stone, 18x10x8", 12" in the ground for ¼ sec. cor. mkd: ¼ on W face, from which
A chinquapin, 5" dia. bears N.52°E., 41 lks. mkd: ¼ S32 BT
No other tree in limits, & raised a mound of stone, 2 ft. base, 1½" high, W of cor.
Pits impracticable.

BLM Dependent resurvey by James E. Jelley, Cadastral Surveyor under Group #350 & 929 surveyed May 1978/May 1980 - (DCSO records Vol. 42 Page(s) 16346-7)

The ¼ sec. cor. of secs. 31 & 32, monumented with the orig. basalt stone, 18x10x8", loosely set 6" in the ground, and in a mound of stone, 3 ft. base, 1 ft. high, mkd. ¼ on W face, from which the remains of an original bearing tree:
A root hole, bears N.52°E., 44 lks., with a down chinquapin alongside, size indeterminate, no marks visible.
and the remains of a bearing tree of which I have no record
A fir snag, 25" dia., bears S.4¾°W., 74 lks., with fragmentary scribe marks visible on open and burned blaze.

At the corner point
Set an iron post, 28" long, 2½" dia., 20" in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.
T25S R1W
¼
S 31|S 32
1980

from which new BTs
A fir, 15" dia., bears S.64°E., 39½ lks., mkd: ¼ S32 BT.
A fir, 8" dia., bears S.83½°W., 16½ lks., mkd: ¼ S31 BT.
Deposit corner stone alongside iron post.