

TOWNSHIP 25 RANGE 01 POINT IDENTIFIER # 200240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 29 & 30

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Hezekiah H. Johnson, under Contract #721, dated May 1, 1900 (DCSO records Vol. 9 Page(s) 3556-7)

Set a dogwood post, 3 ft. long, 3" sq., 24" in the ground, for ¼ sec. cor., mkd: ¼ S30 on W & S29 on E faced, from which
A chinquapin, 8" dia. bears N.27°E., 38 lks. mkd: ¼ S29 BT
A dogwood, 5" dia., bears N.45°W., 6 lks., mkd: ¼ S30 BT.

BLM Dependent resurvey by James E. Jelley, Cadastral Surveyor under Group #350 & 929 surveyed May 1978/May 1980 - (DCSO records Vol. 42 Page(s) 16349)

Point for the ¼ sec. cor. of secs. 29 & 30. at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post. 28" long, 2½" dia., 24" in the ground, with brass cap mkd.

T25S R1W
¼
S 30|S 29
1978

from which

A fir, 12" dia., bears N.56¾°E., 50 lks., mkd. ¼ S29 BT.
A fir, 10" dia., bears N.47°W., 47 lks., mkd. ¼ S30 BT.