

PRIMARY CORNER DESCRIPTION Cor. Secs 17, 18, 19, & 20

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO Survey by Hezekiah H. Johnson, under Contract #721, dated May 1, 1900 (DCSO records Vol. 9 Page(s) 3560)  
-----  
Set a cedar post, 3 ft. long, 4" sq., 24" in the ground for cor. of secs. 17, 18, 19, & 20, mkd T25S S17 on NE, R1W S20 on SE, S19 on SW & S18 on NW faces, with 3 notches on S & 5 notches on E edges, from which  
A yew, 8" dia. bears N.22°E., 20 lks. mkd: T25S R1W S17 BT  
A hemlock, 16" dia., bears S.29°E., 32 lks., mkd: T25S R1W S20 BT.  
A yew, 10" dia. bears S.57°W. 40 lks. mkd: T25S R1W S19 BT  
A cedar, 14" dia., bears N.48°W., 42 lks., mkd: T25S R1W S18 BT.

Burt W. Holt - For: Hult Lumber Co. - Wit. C. Halverson - March 27, 1960 - C.S. File 51/71-2  
-----  
As determined by old BTs:  
16" Hemlock S.29°E. 21.1 ft., gone.,  
8" Yew N.22°E. 13.2 ft., fd. standing & dead with scribes burned off.  
10" Yew S.57°W. 26.4 ft., fd. standing & dead with scribed clearly vis.  
14" Cedar N.48°W. 27.7 ft., fd. down. & nearly gone but scribes vis.  
Set - 1/2" x 36" Iron Pipe from which:  
10" D.Fir bears S.74°W. 23.0 ft. mkd. S19 BT.  
10" D.Fir bears N.45°30'W. 19.7 ft. mkd. T25S R1W  
9" D.Fir bears S.85°E. 16.4 ft. mkd. S20 BT.  
9" D.Fir. bears N.11°30'E. 34.2 ft. mkd. S17 BT.  
This corner is on a SE slope in old burn with heavy stand of reproduction.

BLM Dependent resurvey by James E. Jelley, Cadastral Surveyor under Group #350 & 929 surveyed May 1978/May 1980 - (DCSO records Vol. 42 Page(s) 16352)  
-----  
The cor. of secs. 17, 18, 19, & 20, perpetuated & recorded by Holt, in 1960, monumented with an iron pipe, 1/2" dia., firmly set, projecting 2" above ground, from which the remains of an original bearing tree:  
A root hole, bears S.57°W., 40 lks., with a down yew alongside, 9" dia., with fragmentary scribe marks visible on open blaze.  
and bearing trees mkd. by Holt  
A fir, 15" dia., bears N.11½°E., 51½ lks., with healed blaze.  
continued next page

TOWNSHIP 25 RANGE 01 POINT IDENTIFIER # 200400

PRIMARY CORNER DESCRIPTION Cor. Secs. 17, 18, 19, & 20

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

A fir, 15" dia., bears S.85°E., 25½ lks. dia., with healed blaze.

A fir, 12" dia., bears S.74°W., 35½ lks., with healed blaze.

A fir, 15" dia., bears N.45½°W., 29½ lks., with healed blaze.

At the corner point

Set an iron post. 28" long, 2½" dia., 24" the ground, with brass mkd:

T25S	R1W
S 18	S 17
S 19	S 20
1978	

Reset iron pipe alongside iron post.

Fd. Ok by R. Geisler, 10/30/1984 - C.S. File 58/146-15

BLM resurvey by A. Bert Skeesick & Daniel E. Weller, Cadastral Surveyors under Group #1888, surveyed Sept. 1998/Sept. 1999 - (DCS0 rec. Vol. 53 Page(s) 20695-6)

-----  
Cor. of secs. 17, 18, 19, & 20, perpetuated by Holt, in 1960, from original evidence no longer in existence, monumented with an iron post, 2½" dia., firmly set, flush with the ground, with brass cap (properly) mkd.

from which the remains of bearing trees mkd. by Holt

A fir, 17" dia., bears N.11½°E., 51½ lks., with healed double blaze.

A sawed fir stump, 16" dia., bears S.85°E., 25½ lks., with healed double blaze.

A sawed fir stump, 14" dia., bears S.74°W., 35½ lks., with healed double blaze.

A sawed fir stump, 15" dia., bears N.45½°W., 29½ lks., with healed double blaze.

and new bearing trees

A hemlock, 9" dia., bears S.80½°E., 29 lks., mkd. T25S R1W S20 BT.

A fir, 4" dia., bears S.65½°W., 38 lks., mkd. X BT.

A hemlock, 6" dia., bears N.55½°W., 32 lks., mkd. X BT.

From this point, the BLM Geodetic Control Station No. EC 41278 at lat. 43°23'39.318"N., long. 122°50'34.095" W. (NAD 1983 (91)), determined by the NAVSTAR Global Positioning System, bears N.66°06'22"W., 14.021 chs., (mean bearing & sea level.) monumented with an alum. cap, ¾" dia., firmly set flush with the ground, with top mkd. EC 41278 GPS 1998.