

TOWNSHIP 25 RANGE 01 POINT IDENTIFIER # 200440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 17 & 18

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Hezekian H. Johnson, Deputy Surveyor, under Contract #721, dated May 1, 1900 (DCSO rec. Vol. 9 Page 3563)

Set a basalt stone, 15x8x5", 10" in the ground for ¼ sec. cor. marked ¼ on W face, from which

A Cedar, 24" dia., bears S.63°E., 51 lks., mkd: ¼ S17 BT.

A Fir, 14" dia., bears S.83°W., 60 lks., mkd: ¼ S 18 BT.

BLM resurvey by A. Bert Skeesick & Daniel E. Weller, Cadastral Surveyors under Group #1888, surveyed Sept. 1998/Sept. 1999 - (DCSO rec. Vol. 53 Page(s) 20696-7)

Point for the 1/4 sec. cor. of secs. 17 & 18, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 28" long, 2½" dia., 25" in the ground, in a collar of stone, 2 ft. dia., with brass cap mkd.

T 25 S R 1 W

 ¼
S 18 | S 17

1999

from which

A hemlock, 9" dia. bears S.79¾°E., 28 lks., mkd. ¼ S17 BT.

A fir, 14" dia., bears N.20¾°W., 21 lks., mkd. ¼ S18 BT.

Deposit a magnet in a white plastic case at the base of the stainless steel post.