

PRIMARY CORNER DESCRIPTION Cor Secs 7, 8, 17, & 18

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Hezekiah H. Johnson, under Contract #721, dated May 1, 1900 (DCSO records Vol. 9 Page(s) 3563-4)

Set a basalt stone, 16x12x10", 11" in the ground for cor. of secs. 7, 8, 17, & 18, marked with 4 notches on S & 5 notches on E edges, from which

A chinquapin, 6" dia., bears N.45°E., 34 lks., mkd: T25S R1W S8 BT.

A fir, 14" dia. bears S.30°E. 75 lks. mkd: T25S R1W S17 BT

A fir, 24" dia. bears S.40°W. 72 lks. mkd: T25S R1W S18 BT

A hemlock, 20" dia., bears N.53°W., 82 lks., mkd: T25S R1W S7 BT.

BLM Resurvey by Lynn M. Roseberry, Cadastral Surveyor, under Group #353, Surveyed July/Aug. 1957 - (DCSO records Vol. 28 Page(s) 12140)

The cor. of secs. 7, 8, 17 & 18, monumented with a basalt stone, 16x12x10", firmly set 11" in the ground, marked with 5 grooves on E & 4 grooves on S face; from which the remaining original bearing trees:

A fir, 25" dia., bears S.30 E., 67½ lks., with a healed blaze. (Record dist., 75 lks,)

A fir snag, 35" dia., bears S.39°W., 67½ lks., with scribe marks S 8 visible on partly opened blaze. (Record S.40°W., 72 lks.)

At the corner point

Set an iron post, 30" long, 2" dia., 20" in the ground, to solid rock, in. a mound of stone, 3 ft. base, to top, with brass cap marked

T25S	R1W
<u>S 7</u>	<u>S 8</u>
S 18	S 17
1957	

from which

A chinquapin, 5" dia., bears N.49°E., 31 lks., mkd: T25S R1W S8 BT.

A fir, 35" dia., bears S.22½°W., 108½ lks., mkd: T25S R1W S18 BT.

A fir, 20" dia. bears N.67°W., 73 lks. mkd: T25S R1W S7 BT

Deposit the basalt stone alongside the base of the iron post

Fd 1957 BC & 4 live BTs. Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Oct. 1966 - C.S. File 52/30-23A

FD. Ok 11/1984 R. Geisler, C.S. File 58/146-14

continued next page

PRIMARY CORNER DESCRIPTION Cor. Secs. 7, 8, 17, & 18

Alias	Description
Alias	Description
Alias	Description
Alias	Description

BLM resurvey by A. Bert Skeesick & Daniel E. Weller, Cadastral Surveyors under Group #1888, surveyed Sept. 1998/Sept. 1999 - (DCSO rec. Vol. 53 Page(s) 20698)

Cor. of secs. 7, 8, 17, & 18, monumented with an iron post, 2½" dia., firmly set, projecting 8" above ground, in a mound of stone, 3 ft. base, to top, with brass cap (properly) mkd. from which the remains of the original bearing trees

A fir, 34" dia., bears S.30°E., 67½ lks., with a healed blaze.

A fir snag, 32" dia., bears S.39°W., 65½ lks., with a rotted blaze. (Record, 67½ lks.)

and bearing trees mkd. by Roseberry

A chinquapin, 8" dia., bears N.49°E., 31 lks., with illegible scribe marks visible on partially healed rotted blaze.

A fir, 40" dia., bears S.22½°W., 107 lks., with a healed blaze. (Record, 108½ lks.)

A fir, 29" dia., bears N.67°W., 73 lks., with a healed blaze.

and a new bearing tree

A fir, 10" dia., bears N. 59¼° E., 16 lks., mkd. X BT