

TOWNSHIP 25 RANGE 01 POINT IDENTIFIER # 200540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 7 & 8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>GLO Survey by Hezekiah H. Johnson, under Contract #721, dated May 1, 1900 (DCSO records Vol. 9 Page(s) 3566)</p> <p>-----</p> <p>The point for ¼ sec. cor., falls on a basalt stone, in place, 24x12x7" above ground which I mark, at the exact cor. point, with a cross (+) and ¼ W of cross for ¼ sec. cor. from which A cedar, 14" dia., bears S.77½°E., 28 lks., mkd: ¼ S8 BT. A fir, 15" dia., bears West, 40 lks., mkd: ¼ S7 BT.</p>
<p>Douglas Co. Surveyors Office - James W. Byron, Deputy - Milo Godfrey - Clete Putnam - July 13, 1960 - C.S. File 52/30-1</p> <p>-----</p> <p>Found - Basalt stone as recorded Orig. SE BT shows good scar & is in good condition. Orig. West BT is down, shows good scar. New BT - 15" Hemlock S.86°W., 10.0 ft. scribed ¼ S7 CS BT.</p>
<p>Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - E. West - Oct. 1966 - C.S. File 52/30-23</p> <p>-----</p> <p>Found - Orig. Basalt Stone 24x12x7" above ground mkd "¼ X" on top, very solid. 15" now 16" Hemlock S.86°W., 10.0 ft., shows "¼ S7 CS BT" on unhealed blaze. Both Orig. BTs destroyed by logging. Because of size & rigidity of Stone, we do not set Brass Cap. New BTs- 60" Fir Stump N.65°E. 25.5 ft. mkd. ¼ S8 CS BT. 19" Hemlock N.6°W., 13.1 ft., mkd. S7 CS BT. Note - Corner lies 40 ft. west of small creek, course S.15°W.</p>
<p>Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff Lorsung- 5/8/2023 - C.S. File 67/56-14</p> <p>-----</p> <p>Found - Unrecorded 3½" GLO survey drill cap, set near center-south edge of corner stone. Burned-dead 30" hemlock S.86°W., 10.0 ft. fully healed single blaze add 3½" mag nail right side center. Burnt-dead 28" hemlock N.6°W., 13.1 ft. fully healed single blaze add 3½" mag nail right side center. Unrecorded 24" D.Fir S.3°E., 23.0 ft. (per tag) tree burned-dead add 3½" mag nail right side center. A galv. Metal lath is south 1± ft. New - Burnt-dead 14" D.Fir S.22°E., 19.6 ft., 3½" mag nail right side center, tree not blazed or scribed.</p> <p>Continued next page</p>

TOWNSHIP 25 RANGE 01 POINT IDENTIFIER # 200540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 7 & 8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Note - Corner is approx. 300' north of gravel road. Corner
lies 50 ft (rec. 40') west of small creek, course
S.15°W)
Area burnt 9/2020
Compass decl. 14½°E.
Lat: 43°24'55.70"N Long: 122°50'29.48"W