

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 5 & 6

Alias	Description

<p>GLO Survey by Hezekiah H. Johnson, under Contract #721, dated May 1, 1900 (DCSO records Vol. 9 Page(s) 3569)</p> <p>-----</p> <p>Set a hemlock post, 3 ft. long, 3" sq., 24" in the ground for ¼ sec. cor. mkd. ¼ S6 on W &amp; S5 on E faces, from which</p> <p>    A fir, 6" dia., bears S.30°E., 48 lks., mkd: ¼ S5 BT.</p> <p>    A pine, 5" dia., bears S.42°W., 19 lks., mkd: ¼ S6 BT.</p>
<p>Reported as not found by Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Oct. 1966 - C.S. File 52/30-24A</p>
<p>BLM Dependent resurvey by James E. Jelley, Cadastral Surveyor under Group #1061 surveyed April/June 1981 - (DCSO records Vol. 45 Page(s) 17359)</p> <p>-----</p> <p>Point for the ¼ sec. cor. of secs. 5 &amp; 6, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28 long, 2½" dia., 24" in the ground with brass cap marked:</p> <p style="text-align: center;">T25S R1W           ¼           S 6   S 5           1981</p> <p style="text-align: right;">from which</p> <p>    A cedar, 6" dia., bears S.78°E., 44½ lks., mkd: ¼ S5 BT.</p> <p>    A hemlock, 6" dia., bears N.59½°W., 137½ lks. mkd: ¼ S6 BT</p>
<p>BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 2500, Surveyed Sept./Nov. 2011 - (DCSO records BLM Plat T25-1W 2012-2 &amp; Vol. 58 Pages 22945-6)</p> <p>-----</p> <p>The ¼ sec. cor. of secs. 5 &amp; 6, monumented with an aluminum post, 2½" dia., firmly set, projecting 2" above ground, with aluminum cap (properly) mkd. (Rec., iron post with brass cap) from which the BTs mkd. by Jelly</p> <p>    A cedar, 23" dia., bears S.78°E., 29.4 ft. with a healed blaze.</p> <p>    A hemlock, 20" dia., bears N.59½°W., 90.8 ft. with a healed blaze.</p> <p>Corner is located 10 ft. S of a draw, drains N.65°e.</p>
<p>Gerald Nygren - For: Barnes &amp; Associates - 12/2018 - M175-10</p> <p>-----</p> <p>Found - 1981 BLM Brass cap per rec.</p> <p>        6" Cedar now 23" bears S.78°E., 29.4' healed blaze.</p> <p>        6" Hemlock, now 20" bears N.59°30'W., 90.8' healed blaze.</p> <p>        Fd. 5' metal post north, 1.0'</p> <p>Set - 5' galv. Metal post west, 4.0'</p>