

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 32 only

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by Hezekiah H. Johnson, Deputy Surveyor, under Contract #721, dated May 1, 1900 - (DCSO records Vol. 8 Page(s) 3504)

Set a sandstone 20x12x4 ins., 15" in the ground for ¼ sec. cor. marked ¼ on N. face, from which

A Maple 5" dia., bears S.8½°W., 15 lks. dist. mkd. ¼ S5 BT.

A Maple 4" dia., bears N.21½°W., 62 lks. dist. mkd. ¼ S32 BT.

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #797, dated April 19, 1910 - (DCSO records Vol. 9 Page(s) 3575) (and duplicate Pg. 4081 Vol. 10)

The ¼ sec. cor. which is a sandstone 5x12x4 ins. above ground, firmly set, marked and witnessed as described by the surveyor general.

I re-establish this cor. in its original position as the ¼ sec. cor. on S. bdy. sec. 32, T25S R1W, only, as follows; Stone above described, already set, from which

A Fir 48" dia., bears N.41½°E., 130 lks. dist. mkd. ¼ S32 BT.

A Maple 4" dia., bears N.21½°W., 62 lks. dist. mkd. ¼ S32 BT.

I obliterate marks on former bearing tree referring to sec. 5.

BLM Remonumentation of corner by James E. Jelley, Cadastral Surveyor, under Group #'s 350 and 929, surveyed May 1978/May 1980 - (DCSO records Vol. 42 Page(s) 16363)

The ¼ sec. cor., monumented with the original sandstone, 20x12x4 ins., loosely set, projecting 10" above ground, and in a mound of stone, 2 ft. base, 1 ft. high, with fragmentary marks visible on N. face, from which a bearing tree mkd. by Mensch:

A Fir 55" dia., bears N.41½°E., 130 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 8" in the ground, to solid rock, mkd. X, supported in a mound of stone, 3 ft. base to top, with brass cap mkd:

T 25 S R 1 W

¼ S 32

1978

from which new bearing trees:

(Cont. Next Page)

TOWNSHIP 25 RANGE 01 POINT IDENTIFIER # 240100

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 32 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A Fir 17" dia., bears N.80¼°E., 53 lks. dist. mkd. ¼ S32
BT.
A Fir 18" dia., bears N.5°W., 60½ lks. dist. mkd. ¼ S32
BT.
Deposit corner stone alongside iron post.