

TOWNSHIP 25 RANGE 01 POINT IDENTIFIER # 240200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 29 & 32

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by Hezekiah H. Johnson, under Contract #721, dated May 1, 1900 (DCSO records Vol. 9 Page(s) 3554)

Set a basalt stone, 20x10x6", 15" in the ground for ¼ sec. cor., mkd. ¼ on N face, & raised a mound of stone, 2 ft. base, 1½ ft. high, N of cor.
Pits impracticable.

BLM Dependent resurvey by James E. Jelley, Cadastral Surveyor under Group #350 & 929 surveyed May 1978/May 1980 - (DCSO records Vol. 42 Page(s) 16348)

Point for ¼ sec. cor. of secs. 29 & 32, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap marked:

T25S R1W
¼ S 29
 S 32
1978

from which

- A fir, 10" dia., bears N.43°W., 30½ lks., mkd: ¼ S29 BT.
- A fir, 14" dia., bears S.14½°E., 9 lks., mkd: ¼ S32 BT.