

TOWNSHIP 25 RANGE 01 POINT IDENTIFIER # 240300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 20 & 29

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by Hezekiah H. Johnson, under Contract #721, dated May 1, 1900 (DCSO records Vol. 9 Page(s) 3558)

Set a basalt stone, 16x9x8", 11" in the ground for ¼ sec. cor. mkd ¼ on N face, from which

A fir, 5" dia., bears N.5°E., 15 lks., mkd: ¼ S20 BT.

A hemlock, 4" dia., bears S.24°E., 6 lks., mkd: ¼ S29 BT.

BLM Dependent resurvey by James E. Jelley, Cadastral Surveyor under Group 689, surveyed May/June 1969 - (DCSO records Vol. 35 Page(s) 14456)

Point for the ¼ sec. cor. of secs. 20 & 29, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 28 long, 2½" dia., 14" in the ground and in a mound of stone, 2 ft. base, to top, with brass cap marked:

¼ $\frac{S\ 20}{S\ 29}$
T25S R1W
1969

from which

A fir, 4" dia., bears N.6°E., 33 lks., mkd: ¼ S20 BT.

A hemlock, 7" dia. bears S.23°E., 52½ lks., mkd: ¼ S29 BT.

Tony Hostetter - For: Seneca Jones Timber Co. - April 2003 - M142-3

Found - Brass cap & accessories as described by BLM in 1969

New BTs- 12" fir, scribed S20 ¼ BT" bears; N.64°E., 19.0 ft to spike.

12" fir, scribed S29 ¼ BT" bears; S 24.W, 19.4 ft to spike.