

TOWNSHIP 25 RANGE 01 POINT IDENTIFIER # 240400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 17 & 20

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Hezekian H. Johnson, Deputy Surveyor, under Contract #721, dated May 1, 1900 (DCSO rec. Vol. 9 Page 3561)

Set a basalt stone, 17x8x5", 11" in the ground for ¼ sec. cor. marked ¼ on N face, from which

A Fir, 22" dia., bears N.15°E., 25 lks., mkd: ¼ S17 BT.

A Fir, 18" dia., bears S.3°E., 42 lks., mkd: ¼ S20 BT.

BLM resurvey by A. Bert Skeesick & Daniel E. Weller, Cadastral Surveyors under Group #1888, surveyed Sept. 1998/Sept. 1999 - (DCSO rec. Vol. 53 Page(s) 20695)

Point for the ¼ sec. cor. of secs. 17 & 20, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 28" long, 2½" diam., 27" in the ground, in a collar of stone, with brass cap mkd.

T 25 S R 1 W

¼ $\frac{S 17}{S 20}$

1999

from which

A fir, 17" dia., bears N.63°E., 24 lks., mkd. ¼ S17 BT.

A fir, 13" dia., bears S.12¼°E., 16 lks., mkd. ¼ S20 BT.

Deposit a magnet in a white plastic case at the base of the stainless steel post.