

TOWNSHIP 25 RANGE 01 POINT IDENTIFIER # 240500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 8 & 17

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by Hezekiah H. Johnson, under Contract #721, dated May 1, 1900 (DCSO records Vol. 9 Page(s) 3564)

Set a basalt stone, 16x10x6", 11" in the ground for ¼ sec. cor. mkd. ¼ on N face, from which
A dogwood, 4" dia., bears N.16°E., 42 lks., mkd: ¼ S8 BT.
A hemlock, 5" dia., bears S.35°W., 12 lks., mkd: ¼ S17 BT.

Bruce Shaner - For: National Plywood, Inc. - Wit. Wm. James & James Griffin - April 21, 1960 - C.S. file 51/92-3

The orig. Surveyor misnamed the BT species as shown following
Orig: Basalt Stone 16"x10"x6", "¼" scratched on north face, from which (The above stone may or may not be present, as a cedar windfall lays over the spot.)
4" Dogwood bears N.16°E., 42 lks.
5" Hemlock bears S.35°W., 12 lks.
Restored: Placed a mark on a cedar windfall (which possibly lays over the orig. stone, from which a:
11" Hemlock, broken off, with scribed visible, bears N.16°E., 42 lks.
8" Yew, with scribes visible bears S.35°W., 12 lks.

BLM resurvey by A. Bert Skeesick & Daniel E. Weller, Cadastral Surveyors under Group #1888, surveyed Sept. 1998/Sept. 1999 - (DCSO rec. Vol. 53 Page(s) 20699)

Point for the ¼ sec. cor. of secs. 8 & 17, at proportionate dist; there is no remaining evidence of the original corner. Set a stainless steel post, 28" long, 2½" diam., 27" in the ground, in a collar of stone, with brass cap mkd.
T25S R1W
¼ S 8
S 17
1999
from which
A fir, 7" dia., bears S.35°W., 41 lks., mkd. ¼ S17 BT.
A fir, 11" dia., bears N.32½°W., 53 lks., mkd. ¼ S8 BT.
Deposit a magnet in a white plastic case at the base of the stainless steel post.