

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 5 & 8

Alias	Description

<p>GLO Survey by Hezekiah H. Johnson, under Contract #721, dated May 1, 1900 (DCSO records Vol. 9 Page(s) 3567)</p> <p>-----</p> <p>Set a chinquapin post, 3 ft. long, 3" sq., 24" in the ground for ¼ sec. cor. mkd: ¼ S5 on N & S8 on S faces, from which A fir, 9" dia., bears S.29°E., 27 lks., mkd: ¼ S8 BT. A chinquapin, 5" dia., bears N.7°W., 8 lks., mkd: ¼ S5 BT.</p>
<p>Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - D. West - Nov. 17, 1966 - C.S. File 52/30-62</p> <p>-----</p> <p>Found - Orig. 9", now 18" Fir Snag, S.29°E. 17.8 ft. Open & find "S" scribe no trace of NW orig. BT. Set - Brass Cap at Cor. mkd: County Surveyors T25S R1W Office ¼ S 5 1966 S 8</p> <p>New BTs- 12" D.Fir S.11°E., 55.7 ft. mkd. ¼ S8 CS BT. 22" I.Cedar N.79°W. 5.9 ft. mkd. ¼ S5 CS BT. 5" Chinquapin N.14°W., 24.6 ft.. mkd. ¼ S5 CS BT.</p> <p>Note - This corner lies on very steep, SW slope, approx. 240 ft. west of top of spur, course north.</p>
<p>Greg Lang - Crew: Trevor Lang - Aug 2014 - C.S. File 65/86-13</p> <p>-----</p> <p>Found - 1966 Douglas Co. brass cap set from orig. evidence. 32" Cedar bears N.79°W., 5.90 ft. (record N.79°W., 5.9 ft.) 22" Fir bears S.11½°E., 55.20 ft. (record S.11°E., 55.7 ft.) 8½" Chinquapin bears N.14½°W., 25.00 ft. (record N.14°W., 24.6 ft.)</p> <p>New - 14" Fir bears S.37¼°W., 25.50 ft. scribed "¼ S8 BT"</p> <p>Note - Bearing is to the center of the tree and distance is measured to spike in the side of the tree. Corner lies on a westerly slope.</p>