

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 28 & 29

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO Survey by Hezekiah H. Johnson, under Contract #721, dated May 1, 1900 (DCSO records Vol. 9 Page(s) 3543)

-----  
Set a basalt stone, 16x8x7" 11" in the ground for 1/4 sec. cor., mkd: 1/4 on W face & raised a mound of stone, 2 ft. base, 1 1/2 ft. high, W of cor. Pits impracticable.

BLM Dependent resurvey by James E. Jelley, Cadastral Surveyor under Group #350 & 929 surveyed May 1978/May 1980 - (DCSO records Vol. 42 Page(s) 16342)

-----  
Point for the 1/4 sec. cor. of secs. 28 & 29, at proportionate dist; there is no remaining evidence of the original corner. Set an iron post. 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd.

T25S R1W  
1/4  
S 29 | S 28  
1978

from which

- A fir, 7" dia., bears S.20°E., 65 lks., mkd. 1/4 S28 BT.
- A fir, 9" dia., bears N.72 3/4°W., 26 lks., mkd. 1/4 S29 BT.

Russell Badgley - For: Seneca Jones Tbr Co - 1/2021 - M178-23

-----  
Found - The original stone with chiseled "X" on top & part of "1/4" on the west side firmly set in place, with a dilapidated pile of stone ±2 ft. west. I set a 1 1/2" iron post, 21" in the ground and bury the stone on the west side, with a collar of stone 2' wide and 8" high, and a 2 1/2" brass cap marked:

T25S R1W  
1/4  
S29 | S28  
2021  
PLS 70716

From which a BT by the BLM IN 1978:

- A 19" D.Fir, burned by fire and now dead (not cut) bears N.60°45'W., 10.5 ft with healed blaze (N.72 3/4°W., 26 lks from 1978 USBLM brass cap)1981
  - NEW BT - A 12" D.Fir, burned by fire & now a 4 ft. high stump with a 6" nail in the top, bears S.18°45'W., 13.4 ft scribed "1/4 S29 BT" on double blaze
  - New RM - A 5/8"x30" iron rod with a 2" alum. cap marked "RM1 2021 PLS70716" bears S.35°18'23"E., 12.79 ft.
- From which a 2 1/2" iron post by Jelley, BLM, 1978, at the proportioned location, firmly set and projecting 8" from the ground with a small collar of stone bears N.84°23'28"E , 7.49 ft, with a 3 1/4" brass cap.

Continued next page

TOWNSHIP 25 RANGE 01 POINT IDENTIFIER # 300240

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 28 & 29

Alias \_\_\_\_\_ Description \_\_\_\_\_

Alias \_\_\_\_\_ Description \_\_\_\_\_

Alias \_\_\_\_\_ Description \_\_\_\_\_

Alias \_\_\_\_\_ Description \_\_\_\_\_

NAD83 (2011):

Latitude: 43°22'17.54223"N Longitude: 122°49'14.40271"W