

TOWNSHIP 25 RANGE 01 POINT IDENTIFIER # 300340

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 20 & 21

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Hezekian H. Johnson, Deputy Surveyor, under Contract #721, dated May 1, 1900 (DCSO rec. Vol. 9 Page 3545)

Set a yew post, 3 ft. long, 3" sq. 24" in the ground for ¼ sec. cor., marked ¼ S20 on W & S21 on E faces, from which
A Yew, 10" dia., bears S.19°E., 8 lks., mkd: ¼ S21 BT.
A Dogwood, 6" dia., bears S.56°W., 13 lks., mkd: ¼ S20 BT.

Reported as not found by Vernon "Ray" Tracy, May 1967 - C. S. file 52/30-78A

BLM resurvey by A. Bert Skeesick & Daniel E. Weller, Cadastral Surveyors under Group #1888, surveyed Sept. 1998/Sept. 1999 - (DCSO rec. Vol. 53 Page(s) 20690-1)

Point for the ¼ sec. cor. of secs. 20 & 21, at proportionate dist.; there is no remaining evidence of the original corner. Set a stainless steel post, 28" long, 2½" diam., 24" in the ground, in a mound of stone, 2½ ft. base to top, with brass cap mkd.

T 25 S R 1 W
 ¼
 |
 S 20 | S 21
 1999

from which

A fir, 27" dia., bears S.48°E., 66 lks., mkd. ¼ S21 BT.
A hemlock, 14" dia. bears S.60¼°W., 21 lks. mkd. ¼ S20 BT.
Deposit a magnet in a white plastic case at the base of the stainless steel post.