

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 16 & 17

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO Survey by Hezekiah H. Johnson, under Contract #721, dated May 1, 1900 (DCSO records Vol. 9 Page(s) 3547)

-----  
Set a fir post, 3 ft. long, 3" sq. 24" in the ground for ¼ sec. cor., marked ¼ S17 on W & S16 on E faces, from which  
A fir, 4" dia., bears N.40°W., 4 lks., mkd: ¼ S17 BT.  
A fir, 5" dia., bears N.28°E., 13 lks., mkd: ¼ S16 BT.

V.W. Hosford - For: Evans Products Co. - April 5<sup>th</sup> thru Nov. 25, 1960 - C.S. File 51/152 & M 20-2

-----  
I failed to find any trace of the orig. corner here, or any trees of the size, noted as BTs.  
At this point I drove a 1½" iron pipe 36" long, 12" above the ground, from which: -  
18" Hemlock bears S.3½°E. 87.5 ft. mkd.- ¼ S16 253 BT.  
6" Chinq. bears N.36°W. 36.2 ft. mkd. ¼ S17 253 BT.

BLM resurvey by A. Bert Skeesick & Daniel E. Weller, Cadastral Surveyor under Group #1888, surveyed Sept. 1998/Sept 1999- (DCSO rec. Vol. 53 Page(s) 20692-3)

-----  
The ¼ sec. cor of secs 16 & 17 reestablished by proportionate measurement by Hosford, in 1960, there is no remaining evidence of the original corner, therefore this position is accepted as a careful and faithful reestablishment of the original corner; determined at record bearing & dist. from the remains of a bearing tree mkd. by Hosford

A fir snag, 17" dia., bears S.3½°E., 133 lks., with scribe marks S25 BT visible on partially healed blaze.

At the corner point

Set a stainless steel post, 28" long, 2½" dia., 26" in the ground, with brass cap mkd. T25S R1W

¼  
S17 | S 16  
1999

from which

A fir, 5" dia., bears N.73¾°E., 17 lks., mkd. ¼ S16 BT.

A hemlock, 6" dia., bears N.20¾°W., 25 lks. mkd. ¼ S17 BT.

Deposit a magnet in a white plastic case at the base of the stainless steel post.