

PRIMARY CORNER DESCRIPTION Cor Secs 4, 5, 8, & 9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Hezekiah H. Johnson, under Contract #721, dated May 1, 1900 (DCSO records Vol. 9 Page(s) 3549-50)

-----  
Set a basalt stone, 16x8x6", 11" in the ground for cor. of secs. 4, 5, 8 & 9, mkd with 5 notches on S & 4 notches on E edges, from which

- A Hemlock, 12" dia., bears N.30°E., 47 lks. mkd T25S R1W S4 BT.
- A hemlock, 5" dia., bears S.32°E., 37 lks., mkd: T25S R1W S9 BT.
- A cedar, 16" dia., bears S.20°W., 25 lks., mkd: T25S R1W S8 BT.
- A hemlock, 10" dia., bears N.21°W., 44 lks., mkd: T25S R1W S5 BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - D. West - Nov. 17, 1966 - C.S. File 52/30-63

-----  
 Found - Orig. corner stone 12x6x5" mkd with 4 notches on E & 5 notches on S faces  
 Orig. 10", now 20" Hemlock, N.21°W., 29.0 ft. Open & find "25 R" Scribe.  
 Orig. SW BT, turned out & lying downhill from corner, shows "1 S8" scribe on unhealed blaze.

Set - Brass Cap at cor. mkd: County Surveyors T25S R1W  
 (Set. Rock Alongside) Office S 5 | S 4  
 1966 S 8 | S 9

New BTs- 16" Hemlock N.80°W., 24.0 ft. mkd. T25S R1W S5 CS BT  
 17" R.Cedar S.22°W., 56.5 ft. mkd T25S R1W S8 CS BT.  
 14" Hemlock S.70°E., 65.1 ft. mkd T25S R1W S9 CS BT.  
 6" Hemlock N.71½°E. 54.5 ft. mkd. S4 CS BT.

Note - This corner lies on NE slope 15 ft. west of creek, course N

BLM Dependent resurvey by James E. Jelley, Cadastral Surveyor under Group #350 & 929 surveyed May 1978/May 1980 - (DCSO records Vol. 42 Page(s) 16344-5)

-----  
The cor. of sees. 4, 5, 8, & 9, perpetuated & rec'd by Tracy, in 1966, monumented with an iron post, 1¼" dia. firmly set projecting 10" above ground, with brass cap (properly) mkd from which the remains of the original BTs

- A root hole, bears S.20°W., 25 lks., with a down cedar alongside, 22" dia., with fragmentary scribe marks visible on open blaze.
- A hemlock, 22" dia., bears N.21°W., 44 lks. with frag. scribe marks visible on open blaze.

continued next page

TOWNSHIP 25 RANGE 01 POINT IDENTIFIER # 300600

PRIMARY CORNER DESCRIPTION Cor Secs 4, 5, 8, & 9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

and bearing trees mkd. by Tracy  
A hemlock, 8" dia., bears N.71½°E., 82½ lks., with fragmentary scribe marks visible on open blaze.  
A hemlock, 15" dia., bears S.70°E., 98½ lks., with fragmentary scribe marks visible on open blaze.  
A cedar, 20" dia., bears S.22°W., 85½ lks., with fragmentary scribe marks visible on open blaze.  
A hemlock, 18" dia., bears N.80°W., 36½ lks., with fragmentary scribe marks visible on open blaze.

Greg Lang - Crew: Trevor Lang - Aug 2014 - C.S. File 65/86-15  
-----

Found - Brass cap set in 1966.  
16" Hemlock bears N.70¼°E., 53.70 ft. (record N.71½°E., 54.5 ft.)  
28" Hemlock bears S.71¼°E., 66.30 ft. (record S.70°E., 65.1 ft.)  
19" R.Cedar bears S.19¼°W., 57.30 ft. (record S.22°W., 56.5 ft.)  
New BT - 11" R.Cedar bears N.63¼°W., 23.30 ft. scribed "T25S R1W S5 BT"  
Note - Bearing is to the center of the tree and distance is measured to spike in the side of the tree.  
Corner lies on a northeasterly slope 15 ft West of Creek.

Fd as per record 11/2017 - M173-75 by G Nygren