TOWNSHIP 25 RANGE 01 POINT IDENTIFIER # 300640

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 4 & 5

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

---

GLO Survey by Hezekiah H. Johnson, under Contract #721, dated May 1, 1900 (DCSO records Vol. 9 Page(s) 3552)

---

Set a fir post, 3 ft. long, 3" sq. 24" in the ground for ¼ sec. cor. mkd: ¼ S5 on W & S4 on E face, from which
A fir, 5" dia., bears West., 16 lks., mkd: ¼ S5 BT.
A Pine, 4" dia., bears S.15°E., 10 lks., mkd: ¼ S4 BT.

---

Reported as not found by Vernon "Ray" Tracy, Nov. 1966 - C.S. File 52/30-55A

---

BLM Dependent resurvey by James E. Jelley, Cadastral Surveyor under Group #350 & 929 surveyed May 1978/May 1980 - (DCSO records Vol. 42 Page(s) 16345)

---

Point for the ¼ sec. cor. of secs. 4 & 5, at proportionate distance; there is no remaining evidence of the orig corner. Set an iron post. 28", long, 2½" dia., 24" in the ground, with brass cap mkd. T25S R1W

¼
S 5 | S 4
1978

from which
A fir, 30" dia., bears S.64½°E., 14½ lks., mkd: ¼ S4 BT.
A fir, 15" dia., bears N.60°W., 22½ lks., mkd: ¼ S5 BT.

---

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff Lorsung- 9/6/2022 - C.S. File 67/54-16

---

Found - BLM 3¼" brass cap on 2" I.D. iron pipe up 1". 1978
A 34" D.Fir S.64½°E., 8.8 ft. (rec. 24½ lks) healed single blaze, add 3½" mag nail right side center.
A 17" D.Fir N.60°W., 14.3 ft. (rec. 22½ lks) healed single blaze, add 3½" mag nail right side center.
New - 5/8"x 30" I.Rod with DCSO yellow plastic cap N.67½°W., 152.0 ft. up 14"
5/8"x 30" I.Rod with DCSO yellow plastic cap N.31°W., 125.8 ft. up 13"
Iron rods set on North road shoulder.
Note - On moderately steep NW slope. Rock outcrop ENE 30± ft
Area burnt 9/2020
Compass decl. 14½°E.
See sketch in file.
Lat: 43°25'47.75"N Long: 122°49'16.11"W

---