

TOWNSHIP 25 RANGE 01 POINT IDENTIFIER # 300660

PRIMARY CORNER DESCRIPTION N 1/16 Secs 4 & 5

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM Dependent resurvey by James E. Jelley, Cadastral Surveyor under Group #350 & 929 surveyed May 1978/May 1980 - (DCS0 records Vol. 42 Page(s) 16346)

-----  
Point for the N 1/16 sec. cor. of secs. 4 and 5 located in paved road, 30 lks. wide, bears N.60°E., and S.60°W.  
Set an iron post, 14" long, 2½" dia., 18 ins. in the ground, the top 4" below road surface, with brass cap mkd.

N 1/16  
S 5 | S 4  
1978

from which

An iron post, 28" long, 2½" dia., set 24" in the ground, and in a mound of stone, 3 ft. base, to top, for a reference monument, bears N.53°E., 75½ lks. dist., with brass cap mkd. N 1/16 S4 RM 1978 and an arrow pointing to the corner.

An iron post, 28" long, 2½" dia., set 24" in the ground, and in a mound of stone, 3 ft. base, to top, for a reference monument, bears N.56¾°W., 140 lks. dist., with brass cap mkd. N 1/16 S5 RM 1978 and an arrow pointing to the corner.

Douglas Co. Surveyors Office - Crew: Stephen Flauser & Jeff Lorsung- 8/8/2023 - C.S. File 67/56-54

-----  
Found - BLM brass cap buried below road surface, good mag reading, not dug up.

¾" brass cap N.53°E., 49.8 ft. flush with surface in mound of stones marked N 1/16 S4 RM 1978 with arrow pointing to corner.

¾" brass cap N.66¾°W., 92.4 ft. (rec. N.56¾°W.) in mound of stones marked N 1/16 S5 RM 1978 with arrow pointing to corner.

New - Add line crossing tag to 11" D.Fir North 22'±

Note - Area burnt 9/2020  
Compass decl. 14½°E.

Oregon Coordinate Reference System  
Cottage Grove - Canyonville Zone  
N 219239.132 E 300179.971