

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 4 & 9

Alias	Description
Alias	Description
Alias	Description
Alias	Description

I, James W. Byron, looked for this corner on December 28, 1966, at the request of Tom Shrum as he had recently found possible scribe marks on a small chinquapin tree.

I do not believe the chinquapin is a bearing tree for the corner or the corner tree as called for in the original notes for the following reasons :

1. There is some doubt the marks observed on this date are actually scribe marks.
2. Record calls for the corner tree to be 4" diameter in 1900. We find this tree to be 2" diameter at this time.
3. Record calls for the corner tree to be marked "¼ S" on north and "S 9" on south face. The marks we find face northwest and no other marks nor axe work was found.
4. We could not get a good ring count, but it does appear the chinquapin is not old enough to be an original
5. We find a chinquapin reasonably close to the position called for the northeast bearing tree. We opened this tree but find no scribing nor axe work.
6. I find no trace of original southwest bearing tree.
7. There are several fir stumps near the chinquapin that, judging by ring count, were at the time of the original survey, more suitable for bearing trees.

Signed: James W. Byron, County Surveyor (See below)

Bruce Shaner - For: National Plywood, Inc. - March 25, 1967 - C.S. File 55/31

The ¼ Section Corner is a 4" Chinquapin tree, now broken and chopped down, but with original bark scribes (Johnson, 1900) still visible (though faint) on the north side of tree; scribes visible were "¼ S". The original (1900) section line blazes were in line (east-west) with this corner.

At the ¼ Section Corner I set a 3" square yew post, scribed "¼S", from which a:

4" Chinquapin probable original bearing tree, but with face freshly chopped off, bears N.28°E., 14.6 ft; (record was N.28°E., 12.5 ft).

Sprouts from probable original Chinquapin BT (tree now missing) bears S.28°W., 5.9 ft.

26" D.Fir bearing tree, stump only, I scribed "¼S S9 BT" bears S.22°W., 33.7 ft.

26" D.Fir bearing tree, I scribed "¼S S4 BT" bears N.46°W., 13.9 ft.

Note - An iron pipe at a proposed ¼ Section Corner set by U.S. Plywood Corp. by proportional measurement, bears N.81¼°W, a distance of 66.0 feet from the corner as found by me.

cont next pg

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 4 & 9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BLM Dependent resurvey by James E. Jelley, Cadastral Surveyor under Group #350 & 929 surveyed May 1978/May 1980 - (DCSO records Vol. 42 Page(s) 16343-4)

From the 1/4 sec. cor. of secs. 4 & 9, perpetuated & recorded by Shaner, in 1967, monumented with the remains of the original corner tree, a chinquapin root crown, 4" dia., from which the remains of an original bearing tree:

A chinquapin root crown, 6" dia., bears N.28°E., 22 lks., no marks visible. (Record, 19 lks.)

and the remains of bearing trees mkd. by Shaner

A sawed fir stump, 26" dia., bears N.49°W., 22½ lks., with fragmentary scribe marks visible on open blaze.

A sawed fir stump, 26" dia., bears S.19½°W., 52½ lks., with scribe marks ¼ S9 BT visible on open blaze.

At the corner point

Set an iron post, 28", long, 2½" dia., 24" in the ground, with brass cap mkd. T25S R1W

¼ $\frac{S\ 4}{S\ 9}$

1978

No suitable trees available within limits.

From this point, a corner established by Shrum, in 1966, & perpetuated by Tracy. in 1966, bears N.81¼°W., 1.00 chs., determined from the remains of BTs mkd. by Shrum:

A cedar snag, 36" dia., bears N.31°E., 14 lks., with fragmentary scribe marks visible on open blaze.

A chinquapin, 10" dia., bears S.41°E., 21 lks., with fragmentary scribe marks visible on open blaze.

A chinquapin, 9" diam., bears S.45°W., 31½ lks., with fragmentary scribe marks visible on open blaze.

and a bearing tree mkd. by Tracy

A chinquapin, 10" diam., bears S.64°E., 16½ lks., with fragmentary scribe marks visible on open blaze.

Fd. & used on BLM Dependent resurvey by Wayne Rogers, Cadastral Surveyor, under Group #1347, surveyed Sept 1986/April 1987 - (DCSO records Vol. 49 Page(s) 18422-3)

Gerald Nygren - For: Barnes & Assoc. - Nov 2017 - M173-75

Found - 1978 BLM brass cap per 1978 resurvey
26" sawed fir stump, 4' tall bears N.49°W., 14.9' visible scribed.

26" sawed fir stump, 2' tall bears S.19°30'W., 34.7' visible scribed.

A 2½" alum. cap mkd: "US PC PROP COR RE 4287" per M32-62 bears N.81°15'W., 66.0' cont. next pg

TOWNSHIP 25 RANGE 01 POINT IDENTIFIER # 340600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 4 & 9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New BTs- 9" D.Fir bears N.65°E., 27.5' scribed: "¼ S4 BT"
6" D.Fir bears S.2°E., 16.0' scribed: "X BT"
6" D.Fir bears N.1°W., 11.4' scribed: "X BT"
7" chinquapin bears S.80°W., 7.3' scribed: "X BT"