

TOWNSHIP 25 RANGE 01 POINT IDENTIFIER # 340640

PRIMARY CORNER DESCRIPTION Center 1/4 Cor Sec 4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Thomas Shrum, Jr. - For: US Plywood Cor. - Nov. 1966 - M32-63

Set - 2½" dia., alum. cap.
15" W.Pine stump S.56½°E., 18.3 ft.
13" D.Fir stump N.88°W., 15.0 ft.

BLM Dependent resurvey by James E. Jelley, Cadastral Surveyor under Group #350 & 929 surveyed May 1978/May 1980 - (DCSO records Vol. 42 Page(s) 16354)

Point for center ¼ sec. cor. of sec. 4, at intersection with the E & W center line.
Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap marked:
T25S R1W
C ¼ S 4
1978
from which
A fir, 8" dia., bears N.84°E., 5½ lks., mkd: C¼ S4 BT.
A hemlock, 10" dia. bears N.72½°W., 75½ lks. mkd: C¼ S4 BT
From this point, a corner established by Shrum in 1964, bears N.71¼°W., 0.50 chs., monumented with an iron post 1½" dia., firmly set, projecting 10" above ground, with aluminum cap mkd. T25S R1W S¼ Sec 4 1964, from which the remains of a bearing tree mkd. by Shrum:
A sawed fir stump, 20" dia., bears N.88¼°W., 22½ lks., with fragmentary scribe marks visible on open blaze.

Fd. as per 1978 BLM survey 11/2017 - by G. Nygren

Douglas Co. Surveyors Office - Crew: Stephen Flauser & Jeff Lorsung- 7/10/2023 - C.S. File 67/56-46

Condition report
Found - BLM brass cap (properly mkd) up 4"
13" Fir N.84°E., 3.6 ft. good scar.
22" Hemlock N.72½°W., 49.8 ft. good scar.
1½" iron pipe with alum cap N.71¼°W., 33.0 marked:
T25S R1W S¼ S4 1964
Bearings and dist. Not checked due to windfall and brush.
Note - Area burnt 9/2020
Compass decl. 14½°E.
Oregon Coordinate Reference System
Cottage Grove - Canyonville Zone
N 217874.442 E 300108.965