

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 27 & 28

Alias	Description
Alias	Description
Alias	Description
Alias	Description

<p>GLO Survey by Hezekiah H. Johnson, under Contract #721, dated May 1, 1900 (DCSO records Vol. 9 Page(s) 3532)</p> <p>-----</p> <p>Set a basalt stone 20x12x12" 15" in the ground for ¼ sec. cor. marked ¼ on W face, & raised a mound of stone 2 ft. base, 1½ ft. high, W of corner. Pits impracticable.</p>
<p>Romanso E. Ware, LS 1005 - For: USFS - Aug. 1978 - M70-33</p> <p>-----</p> <p>Set - 3" Brass cap on 2½" Galv. I.P. marked: T25S R1W S28 S27 1978 RLS 1005.</p> <p>New - 6" D.Fir, S.44°W., 16.8 ft. "¼ S28 T25S R1W BT" 8" D.Fir, N.70°E., 16.1 ft. "¼ S27 T25S R1W BT" Nailed a brass washer stamped RLS 1005 to lower blaze of each BT.</p>
<p>Russell Badgley - For: Seneca Jones Tmbr Co- 1/2021 - M178-23</p> <p>-----</p> <p>Found - A 2½" galvanized iron post by Ware in 1978, firmly set and projecting 19" above the ground with a mound of stone on the north side, with a 3" brass cap (properly) marked, from which</p> <p>BTs by Ware in 1978 -</p> <ul style="list-style-type: none">A 12" D.Fir, burned by fire & now a 4 ft. high stump with a 6" nail in the top, bears S.39°00'W., 16.5 ft with healed double blaze (S.44°W., 16.8')A 13" D.Fir, burned by fire & now a 4 ft. high stump with a 6" nail in the top, bears N.62°30'E., 16.0 ft with healed double blaze (N.70°E., 16.1') <p>New RMs- A 5/8"x30" iron rod with 2" alum. cap mkd. "RM1 PLS70716" bears S.40°35'10"E., 23.33 ft.</p> <p>A 5/8"x30" iron rod with 2" alum. cap mkd. "RM2 PLS70716" bears N.26°53'16"W., 26 48 ft</p> <p>NAD83 (2011): Latitude 43°22'17.68631"N Longitude 122°48'02.13432"W</p>