

PRIMARY CORNER DESCRIPTION Cor. Secs. 21, 22, 27, & 28

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Hezekiah H. Johnson, under Contract #721, dated May 1, 1900 (DCSO records Vol. 9 Page(s) 3532-3)

-----  
Set a basalt stone, 24x10x8" 18" in the ground for cor. of secs. 21, 22, 27, and 28, marked with 2 notches on S & 3 notches on E edges, from which -

A Cedar, 8" dia. bears N.29°E. 41 lks. mkd T25S R1W S22 BT  
A Hemlock, 4" dia. bears S.40°E., 35 lks. mkd T25S R1W S27 BT.

A Chinquapin, 5" dia. bears S.44°W., 20 lks. mkd T25S R1W S28 BT.

A Hemlock, 8" dia., bears N.25°W., 63 lks., mkd T25S R1W S21 BT.

-----  
Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - E. West - May 1967 - C.S. File 52/30-78

-----  
Found - 12x12x14" above ground, Basalt Stone mkd. "X" on top & 2 notches on S & 3 notches on E sides.  
Orig. 4", now 15" Hemlock S.40°E., 23.1 ft. chopped open & find "R1W" scribe. Alive.  
Orig 8" ?, now 11" Cedar, N.29°E. 27.1 ft, prev. opened & shows "T25S R1W S22 BT"., scribe. Alive.  
Orig. 5", now 8" chinquapin, sawed stump, S.44°W., 13.2 ft., possible reverse scribe.  
No trace of NW BT.

Set - Brass Cap at cor. Mkd: County Surveyors T25S R1W  
(Set on S. side of Cor. Office S 21 | S 22  
Stone, 6" S. of "X") 1967 S 28 | S 27

New BTs- 7" Hemlock S.69°E. 17.9 ft. mkd. T25S R1W S27 CS BT.  
7" Cedar S.10°W., 16.6 ft. mkd. T25S R1W S28 CS BT.  
14" Hemlock N.51°W. 18.0 ft. mkd. T25S R1W S21 CS BT  
Orig. BT to NE alive & in good condition scribing OK

-----  
BLM resurvey by A. Bert Skeesick & Daniel E. Weller, Cadastral Surveyor under Group #1888, surveyed Sept. 1998/Sept 1999- (DCSO rec. Vol. 53 Page(s) 20687-8)

-----  
The cor. of secs. 21, 22, 27, & 28, perpetuated by Tracy, in 1967, monumented with a basalt stone, 14x18x12" above ground, firmly set, mkd. with 3 vertical grooves on E & 2 vertical grooves on S edges, & X on top, (with an iron post, 1½" dia., driven alongside, 0.8 lks South of the X, projecting 7" above ground, with brass cap mkd COUNTY SURVEYORS OFFICE T25S R1W S21 S22 S27 S28 R1W 1967, the iron post was set alongside the stone monument & is not accepted as the orig corner position) from which the remains of the orig. BTs

continued next page

PRIMARY CORNER DESCRIPTION Cor Secs 21, 22, 27, & 28

Alias	Description
Alias	Description
Alias	Description
Alias	Description

A cedar, 13" dia., bears N.31¼°E., 41 lks., with scribe marks T25S R1W S22 BT visible on partially opened blaze. (Record, N.29°E.)

A hemlock, 20" dia., bears S.38¼°E., 35 lks., with fragmentary scribe marks visible on partially opened blaze. (Record, S.40°E.)

A rotted chinquapin stump, size indeterminate, bears S.47¼°W., 18 lks., no marks visible. (Record, S.44°W., 20 lks.)

and the remains of bearing trees mkd. by Tracy

A rotted hemlock stump, size indeterminate, bears S.70°E., 28 lks., with rotted trunk, 7" dia., lying alongside, blaze & axe marks visible, no scribing found.

A cedar, 9" dia., bears S.7¼°W., 25 lks., with a healed blaze.

A hemlock, 19" dia., bears N.53½°W., 27 lks., with scribe marks R1W 21S visible on partially opened blaze.

At the corner point

Set a brass tablet, 3" dia., 3½" stem, in a drill hole, 1" dia. in the orig. stone, with top mkd.

T 25 S R 1 W  
S 21 | S 22  
S 28 | S 27  
 1999

Removed the 1967 brass cap from the iron post, leaving the iron post in its original position, at the request of the Douglas County Surveyor's Office.

From this point, the BLM Geodetic Control Station No. EC 41290 at latitude 43°22'45.181"N. longitude 122°47'44.053"W. (NAD 1983 (91)), determined by the NAVSTAR Global Positioning System, bears N.84°42'16"E., 20.552 chs., (mean bearing & sea level dist.) monumented with an alum. cap, 3¼" dia., firmly set flush with the ground, with top mkd. EC 41290 GPS 1999.

Russell Badgley - For: Seneca Jones Tmbr Co- 1/2021 - M178-23

Found - A 3" brass tablet by the BLM in 1999, in original stone firmly set and projecting 12" above the ground (properly) mkd: from which

The original BT -

A 23" Hemlock, burned by fire ac now a 4 ft. high stump with a 6" nail in the top bears S.38°15'E., 23.1 ft w/healed blaze (S.38¼°E. 35 lks) 2002 BLM

BTs by Tracy -

A 13" Cedar, burned by fire & now a 4 ft. high stump with a 6" nail in the top, bears S.7°00'W., 16.9 ft w/healed blaze (S.7¼°W., 25 lks) 2002 BLM

continued next page

TOWNSHIP 25 RANGE 01 POINT IDENTIFIER # 400300

PRIMARY CORNER DESCRIPTION Cor Secs 21, 22, 27, & 28

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A 20" Hemlock, burned by fire & now a 4 ft high stump with a 6" nail in the top, bears N.54°00'W., 17.3 ft in/healed blaze (N.53½°W., 27 lks) 2002 BLM  
New RMs- A 5/8"x30" iron rod with 2" alum. cap marked "RM1 2020 PLS70716" bears N.73°49'05"E., 9.92 ft  
A 5/8"x30" iron rod with 2" alum. cap marked "RM2 2020 PLS70716" bears N.41°21'21"W., 11.4 ft  
The 1½" iron post along side (south 0.8 lks) 2002 BLM  
NAD83 (2011):  
Latitude: 43°22'43.95379"N Longitude: 122°48'02.33015"W