

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs 21 & 22

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO Survey by Hezekiah H. Johnson, under Contract #721, dated May 1, 1900 (DCSO records Vol. 9 Page(s) 3533)

Point on rocky spur, slopes E.
 Set a basalt stone, 20x8x6", 15" in the ground for ¼ sec. cor., marked ¼ on W face, from which
 A cedar, 12" dia., bears N.22½°E., 25 lks., mkd: ¼ S22 BT.
 An arbutus, 15" dia. bears N.58°W., 57 lks., mkd: ¼ S21 BT

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - D. West - Dec. 2, 1966 - C.S. File 52/30-72

Found - Orig. Basalt corner Stone, 16x8x6" set in mound of Stone and marked ¼.
 Orig. 12", now 18" Cedar, N.22½°E. 16.5 ft. Alive, top broken off, shows good scar. We do not open.
 Orig. 15", now 17" Arbutus (Laurel), Alive, N.58°W. 34.3 ft., (recorded as 36.6') Open & find frag. reverse scribe, center rotted.
 Set - Brass Cap at Cor. Mkd: County Surveyors T25S ¼ S21|S22 R1W Office, 1966
 (Set B.Cap in mound of stone & Reset Original Stone)
 New BTs- 8" D.Fir N.19°W. 29.2 ft. Mkd. ¼ S21 CS BT.
 8" D.Fir S.42°E. 13.0 ft. mkd. ¼ S22 CS BT.
 Note - This corner lies on steep East slope on rocky spur.

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 25001006, Surveyed Aug. 2010/April 2011 - (DCSO records Vol. 57 Page(s) 22821)

The ¼ sec. cor. of secs. 21 & 22, perpetuated by the Douglas Co Surveyor's Office in 1966, monumented with an iron post, 1¼" dia., firmly set, projecting 11" above the top of a mound of stone, 3 ft. dia., 1 ft. high, with a brass cap mkd. from which the remains of the original bearing trees
 A roothole bears N.22½°E., 16.5 ft., downhill of which is a down cedar, 18" dia., with no marks visible.
 A triple trunked madrone with a decayed center, trunks each 15" dia., bears N.58°W., 37.6 ft., with no marks visible.
 and BTs mkd. by the Douglas County Surveyor's Office
 A fir, 14" dia., bears S.45¼°E., 13.3 ft., with a healed double blaze.
 A fir, 12" dia., bears N.22°W., 28.5 ft., with a healed double blaze.
 Corner is located on a rocky spur, slopes generally East.
 (NAD 1983 (CORS 96))
 Latitude: 43°23'09.90" N. Longitude: 122°48'02.78" W cont.

TOWNSHIP 25 RANGE 01 POINT IDENTIFIER # 400340

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs 21 & 22

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Russell Badgley - For: Seneca Jones Tmbr Co- 1/2021 - M178-23

Found - A 1½" iron post by DCSO in 1966, firmly set with a
12" high collar of stone and projecting 12" above
the collar, with a 2½" brass cap (properly) mkd
From which the original BTs -

A triple trunked madrone bears N.57°45'W., 35.2 ft
(N.58°W., 37.6') 2012 BLM

BTs by the DCSO in 1966 -

A 15" D.Fir bears S.45°15'E., 13.1 ft w/ healed
double blaze (S.45¼°E., 13.3') 2012 BLM

A 12" D.Fir bears N.22°15'W., 28.9 ft w/healed
double blaze (N.22°W., 28 5') 2012 BLM

New BT - A 18" D.Fir bears N.69°00'E , 16.1 ft scribed "¼ S22
BT" on double blaze

NAD83 (2011):

Latitude 43°23'09.90623"N Longitude 122°48'02.78295"W