

TOWNSHIP 25 RANGE 01 POINT IDENTIFIER # 400440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 15 & 16

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>GLO Survey by Hezekiah H. Johnson, under Contract #721, dated May 1, 1900 (DCSO records Vol. 9 Page(s) 3536)</p> <p>-----</p> <p>Set a basalt stone, 14x10x8", 10" in the ground for ¼ sec. cor., marked ¼ on W face, from which</p> <p> A hemlock, 17" dia. bears S.44°30'E. 4 lks., mkd: ¼ S15 BT</p> <p> A dogwood, 5" dia., bears N.38°W., 24 lks., mkd: ¼ S16 BT.</p>
<p>V.W. Hosford - For: Evans Products Co. - April 5th thru Nov. 25, 1960 - C.S. File 51/152 & M 20-2</p> <p>-----</p> <p>Found - Orig. corner stone in place. BT for Sec. 15 is OK, now 22" dia. BT for sec. 16 was gone.</p> <p>New BT - 12" Hemlock bears S.72¼°W. 35.3 ft mkd: ¼ S16 253 BT</p>
<p>Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - Aug. 1966 - C.S. File 52/30-22</p> <p>-----</p> <p>Found - Basalt stone at corner point 10x10x12" mkd: "X" on top. Orig. 17" Hemlock S.44½°E., 2.6 ft. down & burned, shows scar. 12", now 13" hemlock now dead, S.72¼°W., 35.3 ft., shows scribe on unhealed blaze. 1960</p> <p>Set - Brass cap at cor. mkd: County Surveyors Office 1966 T25S ¼ S16 S15 R1W & place stone alongside. 16" Hemlock S.46°E., 45.1 ft. mkd: ¼ S15 CS BT. 23" D.Fir S.86½°E., 24.2 ft. mkd: ¼ S15 CS BT.</p> <p>Note - Due to logging to W of corner, there are no trees available. Corner lies on N-S cutting line.</p>
<p>Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff Lorsung- 8/16/2022 - C.S. File 67/54-13</p> <p>-----</p> <p>Found - 2½" brass cap on 1" I.D. iron pipe. Orig. stone alongside cap, cap is up 10" D.Fir S.86½°E., 24.2 ft remains is a metal rain cap.</p> <p>Unrecorded BTs possible Forest Service Contract Oct. 2014 LS 2339 on found tag.</p> <p> 8" burned-dead Fir S.24½°E., 6.7 ft., part. healed face, illegible scribes, add 3½" PK nail, right side center.</p> <p> 9" burned-dead D.Fir S.87°W., 3.4 ft., part. healed face, illegible scribes, add 3½" PK nail, right side center.</p> <p>New - 14" burned-dead D.Fir S.11°W., 9.2 ft. 3½" PK nail, right side center, not blazed or scribed. CONT.</p>

TOWNSHIP 25 RANGE 01 POINT IDENTIFIER # 400440

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 15 & 16

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

12" burned-dead D.Fir N.3°W., 18.0 ft. 3½" PK nail,
right side center, not blazed or scribed
Note - Corner is near bottom of N slope 600± ft. from
forest road.
Area burnt 9/2020
Compass decl. 14½°E.
See sketch in file
Lat: 43°24'01.32"N Long: 122°48'03.93"W