

TOWNSHIP 25 RANGE 01 POINT IDENTIFIER # 400540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 9 & 10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Hezekiah H. Johnson, under Contract #721, dated May 1, 1900 (DCSO records Vol. 9 Page(s) 3538)

Set a chinquapin post, 3 ft. long, 3" sq., 24" in the ground for the ¼ sec. cor. marked ¼ S9 on W., S10 on E faces, from which:

A chinquapin, 5" dia. bears N.75°E., 11 lks. mkd: ¼ S10 BT
A chinquapin, 4" dia., bears S.63°W., 10 lks. mkd: ¼ S9 BT

Thomas Shrum, Jr. - For: US Plywood Cor. - Dec. 1966 - M32-63

Set - 2½" dia., alum cap.
Hemlock 8" dia., N.45°W., 7.7'
D.Fir 11" dia., N.40°E., 33.0'

BLM Dependent resurvey by Wayne Rogers, Cadastral Surveyor, under Group #1347, surveyed Sept 1986/April 1987 - (DCSO records Vol. 49 Page(s) 18418-9

Point for the ¼ sec. cor. of secs. 9 & 10, at proportionate distance; there is no remaining evidence of the orig. corner. Set a stainless steel post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd. T25S R1W

¼
S 9|S 10
1987

from which

A hemlock, 6" dia., bears N.88°E., 49 lks., mkd. ¼ S10 BT.
A hemlock, 20" dia., bears S.61½°W., 23 lks., mkd. ¼ S9 BT
Deposit a white "DEEP-1 magnetic marker at the base of the stainless steel post.

From this point, a point established & recorded as the ¼ sec. cor. of secs. 9 & 10 by Shrum, in 1966, bears N.70°37'00" W., 0.250 chs., monumented with an iron post, 1" dia., firmly set, projecting 18" above ground, with a 2½" dia. aluminum cap mkd. TWP 25S R1W ¼ 9 10 RE 4287, from which bearing tree mkd. by Shrum:

A fir, 15" dia., bears S.40°E., 48 lks., with healed blaze
A hemlock, 11" dia., bears N.46½°W., 12 lks., with scribe marks S9 ¼ BT visible on open blaze.

This position was established using improper control: therefore is not used in this resurvey.