

PRIMARY CORNER DESCRIPTION Cor. Secs. 3, 4, 9, & 10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Hezekiah H. Johnson, under Contract #721, dated May 1, 1900 (DCSO records Vol. 9 Page(s) 3539)

-----  
Set a cedar post, 3 ft. long, 4" sq., 24" in the ground for cor. of secs. 3, 4, 9, & 10, mkd. T25S S3 on NE, R1W S10 on SE, S9 on SW & S4 on NW faces with 5 notches on S & 3 notches on E edges, from which

A Dogwood, 7" dia. bears N.20°E. 21 lks mkd T25S R1W S3 BT  
A hemlock, 7" dia., bears S.28°E., 21 lks., mkd: T25S R1W S10 BT.

A dogwood, 6" dia. bears S.20°W. 9 lks mkd: T25S R1W S9 BT  
A chinquapin, 7" dia., bears N.84°W., 20 lks., mkd: T25S R1W S4 BT.

Thomas Shrum, Jr. - For: US Plywood Cor. - Dec. 1966 - M32-63

-----  
Set - 2½" dia., alum cap.  
18" R.Cedar S.10°E., 44.2 ft.  
4" Hemlock N.16½°W., 23.3 ft.  
6" Hemlock S.47°W., 17.7 ft.  
22" R.Cedar N.49°E., 23.0 ft.

BLM Dependent resurvey by Wayne Rogers, Cadastral Surveyor, under Group #1347, surveyed Sept 1986/April 1987 - (DCSO records Vol. 49 Page(s) 18419-20)

-----  
Point for the cor. of secs. 3, 4, 9, & 10, at proportionate dist; there is no remaining evidence of the orig. corner.  
Set a stainless steel post, 28" long, 2½" dia., 22" in the ground, with brass cap mkd.

T25S R1W  
S 4 | S 3  
S 9 | S 10  
1987

from which  
A cedar, 5" dia., bears N.17°E., 35 lks., mkd: X BT.  
A cedar, 17" dia., bears S.62½°E., 42 lks., mkd: T25S R1W S10 BT.  
A fir, 11" dia. bears S.61¼°W. 47 lks. mkd: T25S R1W S9 BT  
A cedar, 8" dia., bears N.50¼°W., 45 lks., mkd: T25S R1W S4 BT.

Deposit white "DEEP-1" magnetic marker at base of stainless steel post.

From this point, a point established & recorded as the cor. of secs. 3, 4, 9, & 10 by Shrum in 1966, bears S.78°40'00"W., 0.730 chs., monumented with an iron post, 1" dia., loosely set, projecting 20" above ground, with a 2½" dia. alum cap mkd. USPL PROPERTY COR TWP 25S R1W 3 4 9 10 RE 4287, from which bearing trees mkd. by Shrum: continued next page

TOWNSHIP 25 RANGE 01 POINT IDENTIFIER # 400600

PRIMARY CORNER DESCRIPTION Cor. Secs. 3, 4, 9, & 10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A cedar, 21" dia. bears N.49°E., 33½ lks. with fragmentary scribe marks visible on partially healed blaze.  
A cedar, 16" dia., bears S.11°E., 66 lks. with fragmentary scribe marks visible on partially healed blaze.  
A hemlock, 9" dia. bears S.45°W., 27 lks. with fragmentary scribe marks visible on partially healed blaze.  
A hemlock, 9" dia. bears N.16°W., 35 lks. with fragmentary scribe marks visible on partially healed blaze.  
This position was established using improper control; therefore is not used in this resurvey.