

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 3 & 4

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO Survey by Hezekiah H. Johnson, under Contract #721, dated May 1, 1900 (DCSO records Vol. 9 Page(s) 3540)

-----  
A fir, 10" dia., I mark ¼ S4 on W, S3 on E sides, for ¼ sec. cor., from which

A fir, 14" dia., bears N.54°E., 12 lks., mkd: ¼ S3 BT.

A chinquapin, 7" dia., bears S.60°W., 8 lks., mkd: ¼ S4 BT

BLM Dependent resurvey by James E. Jelley, Cadastral Surveyor under Group #350 & 929 surveyed May 1978/May 1980 - (DCSO records Vol. 42 Page(s) 16340)

-----  
The ¼ sec. cor. of secs. 3 & 4, monumented with the orig. corner tree, a fir, 13" dia., with healed blaze on W face, from which the remaining original bearing tree:

A fir, 22" dia., bears N.54°E., 12 lks., with fragmentary scribe marks visible on open blaze.

and a reference monument and a new bearing tree

An iron post 28" long, 2½" dia., set 24" in the ground, for a reference monument, bears N.25°E., 13½ lks., with brass cap mkd. ¼ S3 RM 1978 and an arrow pointing to the corner.

A fir, 15" dia., bears N.47°W, 35 lks., mkd. ¼ S4 BT

BLM Dependent resurvey by Wayne Rogers, Cadastral Surveyor, under Group #1347, surveyed Sept 1986/April 1987 - (DCSO records Vol. 49 Page(s) 18422)

-----  
The ¼ sec. cor. of secs. 3 & 4, monumented with the remains of the orig corner tree, a sawed fir stump, 8 ft. high, 13" dia., with scribe marks ¼ S visible on W. face, from which the remaining original bearing tree:

A fir, 26" dia., bears N.54°E., 12 lks., with fragmentary scribe marks visible on opened blaze.

and a reference monument and a bearing tree mkd. by Jelley

An iron post, 2½" dia., firmly set, projecting 4" above ground, bears N.25°E., 13½ lks., with brass cap mkd. ¼ S3 RM 1978 and an arrow pointing to the corner.

A sawed fir stump, 15" dia., bears N.47°W., 35 lks., with scribe marks ¼ S4 BT visible on open blaze.