

PRIMARY CORNER DESCRIPTION So. 1/4 cor. for Sec. 34 only

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Hezekiah H. Johnson, Deputy Surveyor, under Contract #721, dated May 1, 1900 - (DCSO records Vol. 8 Page(s) 3502)

A Pine 8" dia. for ¼ sec. cor. I mark ¼ S34 on N. and S3 on S. sides, from which
 A Pine 8" dia., bears N.31°E., 10 lks. dist. mkd. ¼ S34 BT.
 A Pine 8" dia., bears S.88°E., 18 lks. dist. mkd. ¼ S3 BT

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #797, dated April 19, 1910 - (DCSO records Vol. 9 Page(s) 3573) and (duplicate Pgs. 4080/4079A)

The ¼ sec.cor. which is a Pine 10" dia., marked and witnessed as described by the surveyor general. I re-establish this cor. in its original position as the ¼ sec. cor. on S. bdy. sec. 34, T25s R1W only, as follows:
The Original cor., a Pine, 10" dia., I remark ¼ S34 on N. side, from which
 A Pine 10" dia., bears N.31°E., 10 lks. dist. mkd. ¼ S34 BT.
 A Fir 36" dia., bears N.22°W., 25 lks. dist. mkd. ¼ S34 BT.
I obliterate marks on former bearing tree referring to sec. 3.