

TOWNSHIP 25 RANGE 01 POINT IDENTIFIER # 440500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 10 & 15

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Hezekiah H. Johnson, under Contract #721, dated May 1, 1900 (DCSO records Vol. 9 Page(s) 3537)

Summit of spur slopes N
A Hemlock, 6" dia., I mark ¼ S10 on N, S15 on S sides, for ¼ sec. cor., from which
 A dogwood, 6" dia., bears N.5°E., 26 lks., mkd: ¼ S BT.
 A hemlock, 12" dia., bears S.51°E., 28 lks., mkd: ¼ S BT.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Vernon Tracy - Clete Putnam - June 6, 1962 - C.S. 52/30-9

Found - Hemlock, now 8", at corner. N face opened & good scribing "¼S" visible on old face.
 Hemlock, now 18", S.51°E., 18.5 ft. Has been opened previously & good scribing "¼ S15" visible on old face.
New - 6" Dogwood N.5°E., 17.2 ft., shows scar.
 8" Hemlock N.25°E., 33.2 ft mkd: ¼ S10 CS BT.
 Drive ¾" Iron rod at Base of Corner Tree.

FD. 2 Hemlock stumps & added a L Steel fence post- by Thomas Shrum, Nov. 1968 - C.S. File 55/106

BLM Dependent resurvey by James E. Jelley, Cadastral Surveyor under Group #350 & 929 surveyed May 1978/May 1980 - (DCSO records Vol. 42 Page(s) 16366)

The ¼ sec. cor. of secs. 10 and 15, perpetuated and recorded by Godfrey, in 1962, monumented with the remains of the orig. corner tree, a hemlock stump, 10" dia., no marks visible, from which the remains of the original BTs:
 A sawed dogwood stump, 6" dia., bears N.5°E., 26 lks., no marks visible.
 A sawed hemlock stump, 17" dia., bears S.51°E., 28 lks., with scribe marks 4 S15 BT visible on open blaze.
and the remains of a bearing tree mkd. by Godfrey
 A sawed hemlock stump, 8" dia., bears N.25°E., 51 lks., with scribe marks ¼ S10 CS BT visible on open blaze.
add reference monuments
 An iron post, 28" long, 2½" dia., set 24" in the ground, for a RM, bears North, 16½ lks., with brass cap mkd. ¼ S10 RM 1978 & an arrow pointing to the corner.
 An iron post, 28", long, 2½" dia., set 24" in the ground, for a RM, bears S.69°E., 8 lks., with brass cap mkd. ¼ S15 RM 1978 & an arrow pointing to the corner.

continued next page

1

