

TOWNSHIP 25 RANGE 01 POINT IDENTIFIER # 500140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 34 & 35

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Hezekiah H. Johnson, under Contract #721, dated May 1, 1900 (DCSO records Vol. 9 Page(s) 3518)

A fir, 6" dia., for ¼ sec. cor. I mark ¼ S34 on W & S35 on E sides, from which

A fir, 3" dia., bears N.18°W., 7 lks., mkd: ¼ S34 BT.

A dogwood, 6" dia., bears S.20°E., 14 lks., mkd: ¼ S35 BT.

BLM dependent resurvey by Brian S. Seibold, Cadastral Surveyor under Group #1828, surveyed June/July 1997 - (DCSO records Vol. 53 Page(s) 20325)

The ¼ sec. cor. of secs. 34 & 35, determined at record bearing & distance from the remains of an original BT (The cor. is located in the root hole of the original cor. tree, an uprooted fir, 14" dia. alongside, no marks visible.):

A sawed fir stump, 9" dia., bears N.18°W., 7 lks., with scribe marks ¼ S BT visible on opened double blazes.

(The S is backwards)

At the corner point

Set a stainless steel post, 28" long, 2½" dia., 26" in the ground, with brass cap mkd. T25S R1W

¼
S 34 | S 35
1997

from which new bearing trees

A fir, 27" dia., bears N.36¼°E., 17½ lks., mkd. ¼ S35 BT.

A fir, 11" dia., bears N.57¼°W., 67 lks., mkd. S34 BT.

Deposit a magnet in a white plastic case at the base of the stainless steel post.