

TOWNSHIP 25 RANGE 01 POINT IDENTIFIER # 500200

PRIMARY CORNER DESCRIPTION Cor. Secs. 26, 27, 34, & 35

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Hezekiah H. Johnson, under Contract #721, dated May 1, 1900 (DCSO records Vol. 8 Page(s) 3519)

Set a basalt stone, 21x12x6", 16" in the ground for cor. of secs. 26, 27, 34 & 35, mkd with 1 notch on S & 2 notches on E edges, from which

A Maple, 6" dia., bears N.89°30'E., 12 lks., mkd T25S R1W S26 BT.

A Fir, 18" dia. bears S.23°E., 66 lks. mkd T25S R1W S35 BT

A Cherry, 6" dia. bears S.40°W. 9 lks. mkd T25S R1W S34 BT

A Maple, 8" dia. bears N.51°W. 28 lks. mkd T25S R1W S27 BT

Not found by DCSO, V.R. Tracy, 12/1966 - C.S. File 52/30-72A

BLM dependent resurvey by Brian S. Seibold, Cadastral Surveyor under Group #1828, surveyed June/July 1997 - (DCSO records Vol. 53 Page(s) 20321-2)

The cor. of secs. 26, 27, 34 & 35, determined at record from the remains of the original bearing trees.

A root hole, bears S.81¼°E., 12 lks., with uprooted partially decayed maple trunk, 8" dia., alongside, with fragmentary back scribing visible on partially decayed opened blaze. (Record, N.89½°E.)

A fir, 43" dia., bears S.23°E., 66 lks., with healed blaze. At the corner point

Set a stainless steel post, 28" long, 2½" dia., 26" in the ground, with brass cap mkd.

T25S	R1W
<u>S 27</u>	<u>S 26</u>
S 34	S 35
1997	

from which new bearing trees

A fir, 7" dia. bears N.45°E., 58 lks. mkd. T25S R1W S26 BT

A fir, 43" dia., bears S.18°W., 36½ lks., mkd. T25S R1W S34 BT.

A fir, 11" dia., bears N.79¾°W., 48 lks., mkd. T25S R1W S27 BT.

Deposit a magnet in a white plastic case at the base of the stainless steel post.