

PRIMARY CORNER DESCRIPTION Cor Secs 22, 23, 26, & 27

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Hezekiah H. Johnson, under Contract #721, dated May 1, 1900 (DCSO records Vol. 8 Page(s) 3521)

-----

In bottom of canyon about 600 ft. below summit of ridge. Set a basalt stone, 16x10x6", 11" in the ground for cor. of secs. 22, 23, 26, & 27 mkd with 2 notches on S & E edges from which

A Maple, 6" dia. bears N.66°E. 26 lks. mkd T25S R1W S23 BT

A Hemlock, 7" dia., bears S.68°E., 46 lks., mkd T25S R1W S26 BT.

A Cedar, 12" dia. bears S.71°W. 16 lks mkd T25S R1W S27 BT

A Cedar, 18" dia. bears N.31°W. 51 lks mkd T25S R1W S22 BT

Thomas Shrum, Jr. - For: U.S. Plywood, Inc. - April 19, 1963 - C.S. File 51/254-18

-----

Found - Original Stone

10" Hemlock, S.68°E., 30.4 ft (orig.)

21" Cedar S.71°W., 10.6 ft (orig.)

28" Cedar N.31°W., 33.7 ft (orig.)

7" Maple, N.66°E., 17.2 ft (orig.) (Maple rotten, scribe not legible.

Set - 2½" Aluminum cap.

10" D.Fir, N.40°E., 23.3 ft Mkd: S23 BT.

BLM Dependent resurvey by James E. Jelley, Cadastral Surveyor under Group #350 & 929 surveyed May 1978/May 1980 - (DCSO records Vol. 42 Page(s) 16365)

-----

The cor, of secs. 22, 23, 26, & 27, perpetuated & recorded by Shrum, in 1963, monumented with an iron post 1" dia., firmly set, projecting 4" above ground, with aluminum cap mkd.

T25S	R1W
S 22	S 23
S 27	S 26
1963	

from which an orig BT

A cedar, 28" dia., bears N.31°W., 51 lks. with fragmentary scribe marks visible on open blaze.

and the remains of a bearing tree mkd. by Shrum

A fir snag, 10" dia., bears N.42¾°E., 34½ lks., with scribe marks 23 S BT visible on open blaze.

and new bearing trees

A cedar, 9" dia bears N.48½°E. 47 lks mkd. T25S R1W S23 BT

A hemlock, 6" dia., bears S.79½°E., 85½ lks., mkd. T25S R1W S26 BT.

A yew, 6" dia bears S.59½°W. 104 lks. mkd. T25S R1W S27 BT

continued next page

TOWNSHIP 25 RANGE 01 POINT IDENTIFIER # 500300

PRIMARY CORNER DESCRIPTION Cor Secs 22, 23, 26, & 27

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM Dependent Resurvey by Kenneth W. Saveland, Cadastral Surveyor, under Group No. 25001006, Surveyed Aug. 2010/April 2011 - (DCSO records Vol. 57 Page(s) 22814)

-----  
The cor. of secs. 22, 23, 26, & 27, monumented with an iron post, 1" dia., firmly set, projecting 10 ins. above ground, with an aluminum cap (properly) mkd. from which the remaining original bearing tree  
A cedar, 35" dia., bears N.34¾°W., 33.7 ft., with a healed blaze. (Record, N.31°W.)  
and the remains of a BT mkd. by Shrum, Jr., in 1963  
A sawed fir stump, 11" dia., bears N.37°E., 21.8 ft., with scribe marks S23 BT visible on an open blaze. (Record, N.42¾°E., 22.8 ft.)  
and the remains of bearing trees mkd. by Jelley  
A sawed, decayed cedar stump, 9" dia., bears N.44¾°E., 31.0 ft., with no marks visible. (Record, N.48½°E.)  
A hemlock, 18" dia., bears S.83½°E., 56.4 ft., with a healed blaze. (Record, S.79½°E.)  
A yew, 7" dia., bears S.56¼°W., 68.6 ft., with fragmentary scribe marks visible on a partially healed blaze. (Record, S.59½°W.)  
and a new bearing tree  
A fir, 9" dia., bears N.64°E., 9.0 ft mkd. T25S R1W S23 BT Corner is located on a NW. slope, 13 ft. E. of a creek, 2 ft. wide, course N.15°E.

Douglas McMahan - For: Seneca Jones Tmbr Co. 9/2020 - M177-50

-----  
Found - 1963 2½" Alum. cap on iron pipe  
BTs - 11" D.Fir, bears N.64°E, 9.0 ft "healed face"  
37" R.Cedar bears N.31°W., 33.7 ft "no face"  
11" D.Fir stump, bears N.45°E., 19.0 ft "visible face" (record N.37°E., 21.8 ft)  
18" Hemlock, bears S.79°E., 56.4 ft "healed face" (record S.83°30'E.)