TOWNSHIP 25 RANGE 01 POINT IDENTIFIER # 500640

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 2 & 3

Alias Description
Alias Description
Alias Description
Alias Description

GLO Survey by Hezekiah H. Johnson, under Contract #721, dated May 1, 1900 (DCSO records Vol. 9 Page(s) 3529)

Set a chinquapin post, 3 ft. long, 3" sq., 24" in the ground for ¼ sec. cor. mkd: ¼ S3 on W, S2 on E faces, from which
A hemlock, 13" dia., bears S.88°W., 20 lks., mkd: ¼ S3 BT.
A cedar, 10" dia., bears S.52°E., 17 lks., mkd: ¼ S2 BT.

Douglas Co. Surveyors Office - B. R. Rogers, Deputy & crew - May 25, 1965 - C.S. File 52/30-17

Found - 10" Cedar, now 15", S.52°E., 11.2 ft., scribing visible.
13" Hemlock, now 20", scribing visible.
Rotted remains of Original Stake at Corner.
Set - Brass Cap at Cor. Mkd: County Surveyors Office, 1965

T25S
¼ S 3 | S 2 R1W

New BTs- 7" Hemlock N.50°W., 83.9 ft. Mkd: ¼ S3 CS BT.
7" D.Fir S.20°W., Mkd: ¼ S3 CS BT

Adam DeGroot - For: Seneca Jones Timber Co. - July 2020 - M177-19

Found - A 1½" Iron post by DCSO in 1962 per CS 52/30, firmly set and projecting 3" above the ground, with a 2½" brass cap (properly) marked.
From which the remains of the orig BTs by Johnson in 1900-
A rotted cedar stump bears record (S.52°E., 17 lks) (S.52°E., 11 2')
A rotted hemlock stump bears record (S.88°W., 20 lks)
BTs by DCSO in 1965 -
A 20" D.Fir bears S.18°15'W., 53.8 ft w/healed blaze (S.20'W., no dist.)
A 15" Hemlock bears N.51°15'W., 82.6 ft w/healed blaze (N.50°W., 83.9)
New BTs- A 11" D.Fir bears N.8°30'E., 6.2 ft scribed "¼ S2 BT" on dbl blaze line tree.
A 10" D.Fir bears S.60°30'E., 15.7 ft scribed "¼ S2 BT" on dbl blaze
Lat: 43°25'46.03461"N Long: 122°46'57.92398"W