

TOWNSHIP 25 RANGE 01 POINT IDENTIFIER # 522100

PRIMARY CORNER DESCRIPTION C C for Secs. 1 & 2, T26-1

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Fred Mensch, Deputy Surveyor, under Contract #797, dated April 19, 1910 - (DCSO records Vol. 10 Page(s) 4113)

-----  
At a point 26.28 chs. East of the cor. of secs. 34 and 35, T25S R1W, Set a conglomerate stone 18x12x5 ins., 12" in the ground for closing cor. of secs. 1 and 2, mkd. CC on S. with 1 groove on E. and 5 grooves on W. face, from which  
A Madrone 12" dia., bears S.21°E., 42 lks. dist. mkd. T26S R1W S1 BT.  
A Fir 8" dia., bears S.44°W., 31 lks. dist. mkd. T26S R1W S2 BT.

Maurice E. Farr - For: U.S. Forest Service with Leonard Herzstein and Dave Burr, crew - May 12, 1988 - C.S. File 63/73-3

-----  
Found - 18"x9"x5" water-worn stone laying on the ground with marks "X" on East side (top of stone); CC on N. side; one groove on top and 5 grooves on bottom. I was unable to locate the hole the stone came out of. I use the center of the stone as the position for the corner point.  
A 20" Madrone stump bears S.13°E., 27.7 ft. (Rec. S.21°E., 42 lks.) with no marks visible on partially healed decayed blaze.  
A 30" D.Fir stump S.40°W., 20.2 ft. (Rec. S.44°W., 31 lks. with healed blaze. I chop open and find scribe marks "W" at 8" diameter.  
I place bearing tree tags on both BT stumps.  
Corner is about 150 ft. S. of timber inside a clearcut and 50 ft. E. of a small creek on a steep W. slope. To reach corner from Forest Road #3800-010, turn West onto Rd. #3800-017, drive 1.0 miles and turn left onto Rd. #3800-026, drive 0.5 miles to location poster at clearcut. Corner is approx. 1050 ft. W. of location poster, at the bottom of the clearcut, 1000 ft. lower than road.