

TOWNSHIP 25 RANGE 01 POINT IDENTIFIER # 540200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 26 & 35

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO Survey by Hezekiah H. Johnson, under Contract #721, dated May 1, 1900 (DCSO records Vol. 8 Page(s) 3519-20)

Set a fir post, 3 ft. long, 3" sq., 24" in the ground for ¼ sec. cor., marked ¼ S26 on N., S35 on S faces, from which
A Dogwood, 6" dia., bears N.40°30'E., 11 lks. mkd ¼ S26 BT
A Dogwood, 4" dia., bears S.40°W., 21 lks., mkd ¼ S35 BT

Not found by DCSO, V.R. Tracy, 12/1966 - C.S. File 52/30-72A

BLM dependent resurvey by Brian S. Seibold, Cadastral Surveyor under Group #1828, surveyed June/July 1997 - (DCSO records Vol. 53 Page(s) 20321)

Point for the ¼ sec. cor. of secs. 26 & 35, at proportionate dist., there is no remaining evidence of the original cor. Set a stainless steel post, 28" long, 2½" dia., 26" in the ground, with brass cap mkd.

T25S R1W
¼ $\frac{S\ 26}{S\ 35}$
1997

from which
A hemlock, 8" dia., bears N.31°E., 34½ lks., mkd. ¼ S26 BT
A fir, 26" diam., bears S.51°E., 57 lks., mkd. ¼ S35 BT.
Deposit a magnet in a white plastic case at the base of the stainless steel post.