

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 23 & 26

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO Survey by Hezekiah H. Johnson, under Contract #721, dated May 1, 1900 (DCSO records Vol. 8 Page(s) 3522)

-----

Set a basalt stone 18x16x7" 12" in the ground for 1/4 sec. cor., mkd 1/4 on N face from which

A Cedar, 18" dia., bears S.39°W., 19 lks., mkd 1/4 S26 BT.

A Fir, 10" dia., bears N.35°W., 5 lks. mkd 1/4 S23 BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - E. West - Nov. 28, 1966 - C.S. File 52/30-67

-----

Found - Orig. Basalt Stone 18"x16"x7" mkd. "1/4" on N. face. Orig. 10", now 13" Fir, N.35°W., 3.3 ft. Alive, shows good scar. We do not open.

Orig. 18", now 22' Cedar, S.39°W. 12.5 ft down & out of place. Shows "1/4 SBT" on unhealed blaze.

Set - Brass Cap at Cor Mkd: COUNTY SURVEYORS T25S R1W  
 (set rock Alongside) Office 1/4 S 23  
 1966 S 26

New BTs- 8" D.Fir N.73°W., 23.6 ft. mkd: 1/4 S23 CS BT.  
 5" Cedar S.12°W., 47.2 ft. mkd. 1/4 S26 CS BT.

Note - This corner lies approx. 50 ft. East of NW Cor. of cut off unit.

Douglas Co. Surveyors Office - Larry E. Monrean - R.B. Kimberling - P.L. Earle - May 5, 1977 - C.S. File 59/34-7

-----

Found - No monument fd. Area of corner lies on area cat bladed for fire trail. 1966

Orig. 10" Fir, now dead, 15", bears N.35°W., 3.3 ft. Tree has well healed blaze. We open & find scribing "1/4 S23" Growth rings indicate extremely slow growth.

Orig. 18" now 22" Cedar is down and lodged against NW BT scribing visible in unhealed blaze "1/4 S BT"

A 5" Cedar bearing S.12°W., 47.2 ft. dislodged for cat trail. Has well healed blaze.

A 8" D.Fir bearing N.73°W., 23.6 ft. is uprooted, partially buried, open blaze (unhealed) scribing fd "1/4 S23 CS".

Set - A 1"x30" Iron Pipe 26" in the ground with brass cap attached stamped: "Douglas County Surveyor" T25S R1W  
 1977 1/4 S 23  
 S 26

New - Set RR spike in a 36" Fir stump. Spike bears S.50°W., 37.7 ft. Spike stamped "B.O".

A 12" D. Fir bears N.54 1/2°W., 25.1 ft. Tree double blazed & scribed "1/4 S23 CS BT". cont next page

TOWNSHIP 25 RANGE 01 POINT IDENTIFIER # 540300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 23 & 26

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Note - This corner lies on EW cutting line. Area clear cut to the south.

Douglas McMahan - For: Seneca Jones Tmbr Co. 9/2020 - M177-50

-----  
Found - 1977 DCSO 2½" brass cap on iron pipe  
New BTs- (BLAZED FACE ONLY)  
8" D.Fir bears N.30°E., 14.2 ft.  
16" Hemlock bears N.65°W., 21.0 ft.